

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION WC Cor. Secs. 28, 29, 32, & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors,
under Contract #31 dated April 7, 1853 (DCSO records Vol. 8
Page(s) 3152)

Set post cor. to Secs. 28, 29, 32, & 33, from which
A Yew, 6" dia., bears N.47°E., 14 lks.
A vine-maple, 6" dia., bears S.77°E., 14 lks.
A Fir, 16" dia., bears S.34°W., 40 lks.
An Alder, 20" dia., bears N.36°W., 22 lks.

Douglas Co. Surveyor's Office - John Powell & Crew - Sept.
1970 - C.S. File 52/102-1

Corner not found.
Old fence line no OBTs found. Logged & burned many years ago
- very brushy.

Les Roberts - For: Guistina Resources Inc. - March 2000 -
M134-38

Witness corner

Found - No orig. evidence found.
Set - 5/8" x 30" iron pin by double proportionate measure.
True corner bears N.0°10'08"E., 30.00 ft.
10" Fir N.28°W., 79.9' (scribed/metal washer/painted
red)
14" Fir N.36°W., 11.3' (scribed/metal washer/painted
red)
14" Fir N.61°E., 31.0' (scribed/metal washer/painted
red)
14" Fir N.04°E., 98.8' (scribed/metal washer/painted
red)