

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3153)

-----  
Set post cor. to secs. 20, 21, 28 & 29, from which  
A Y.Oak, 10" dia., bears S.76°E., 25 lks.  
A Laurel, 12" dia., bears N.81°E., 95 lks.  
A Laurel, 16" dia., bears N.82°W., 85 lks.  
A Laurel, 8" dia., bears S.76°W., 106 lks.

Douglas Co. Surveyors Office - Crew: M. Godfrey & S. Bilow - Sept. 2, 1958 (**added 7/11/2017**) - C.S. File 49/83-9

-----  
At approx. location for cor. secs. 20|21|29|28  
Found 1/2" pipe driven through hole in slab of rock approx. 2" thick x 15" square.  
No sign of any BTs could be found. Evidence of very heavy burn all over in near vicinity of corner.

Douglas Co. Surveyors Office - Stephen J. Flauser - Mike Koch - March 19, 2014 - C.S. File 67/41-20

-----  
Found - A 12x12"x4" thick sandstone (roughly square shaped slab) unmarked with a 1/2" dia., thin walled pipe protrudes approx. 12" above ground through hole near center. Stone is on surface of ground tilting north; iron pipe is plumb below stone but is slightly bent and leaning northerly above.  
There is no rec. of this monument having been set. Could be from 1919 surveys in the area. A very old fallen wire fence, running north-south, passes right through monument found.  
Evidence from orig. survey:  
"Top of ascent on NW slope of Hill" is 2.00 chs from found monument (as per orig. rec.)  
Possible evidence of two OBTs:  
No evidence of SE & SW BTs remaining.  
A Laurel, 12" dia., is now a large indistinct root-hole near the record N.81°E., 62.7 ft.  
A Laurel, 16" dia., is now a possible root-hole and stump shelf (formed by root-hole on steep slope) is near the record N.82°W., 56.1 ft.  
New - Evidence found and a confirming GIS quality GPS tie all indicate found stone and IP is likely monumenting orig. corner position.

continued next page

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found stone portion of monument is leveled and plumbed over the found plumb portion of 1/2" dia., iron pipe. The protruding portion of the IP is straightened to be plumb.

A 6" DBH D.Fir scribed "X CS" "BT" on a high-low blaze; bears N.74¼°E., 16.2 ft.

A 6" DBH D.Fir scribed "T24S R6W S28 CS" "BT" on a double blaze; bears S.35½°E., 3.0 ft.

A 6" DBH D.Fir scribed "X" "CS BT" on a double blaze; bears S.28½°W., 29.2 ft.

A 9" DBH Madrone scribed "T24S R6W S20 CS" "BT" on a double blaze; bears N.84°W., 12.9 ft.

Note - Monument is on steep north slope in 60 year old fir and madrone fire reprod. forest.  
Compass decl. 15½°E.