

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3154)

Set post cor. to secs. 16, 17, 20 and 21, from which
A Laurel 10" dia., bears S.15½°E., 39 lks. dist.
A Fir 36" dia., bears N.82½°W., 60 lks. dist.
A Maple 14" dia., bears N.50°E., 79 lks. dist.
A Laurel 8" dia., bears S.18°W., 79 lks. dist.

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3166-67)

The sec. cor. of 16, 17, 20 and 21, Post gone. Reestablished same by setting Fir post 4 ft. long, 4" sq., 24" in the ground, mkd. T24S S16 on NE.; R6W S21 on SE.; S20 on SW.; and S17 on NW. faces, with 3 notches on the South and 4 notches on the E. edges, from which
A Maple 14" dia., bears N.50°E., 79 lks. dist., mkd. T24S R6W S16 BT.
A Laurel 10" dia., bears S.15½°E., 39 lks. dist., mkd. T24S R6W S21 BT.
A Laurel 8" dia., bears S.18°W., 79 lks. dist., mkd. T24S R6W S20 BT.
A Laurel 36" dia., bears N.82½°W., 60 lks. dist., mkd. T24S R6W S17 BT.

Floyd J. Cole, Deputy - Wit: M.F. Riggs; F. Adams; H. Larkin
June 12, 1915 - Field Book 37 Pages 48-50

Renew corner from two original trees, other two missing
A Fir 60" N.88½°W., 53 ft.
A Fir 8" S.7½°W., 28 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; S.A. Bilow, crew - March 26, 1959 - C.S. File 49/83-2

Found - Old 3/4" I.Pipe at corner.
Orig. 10" now 24" Laurel S.15½°E., 25.7 ft. center burned out, shows two good scars, no scribing found.
Badly burned stumps that check bearings and distances, sizes for Cole's BTs and for orig. NW BT. I chained East from top of ridge, checks well.

(Cont. Next Page)

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 6 W
S17 | S16
S20 | S21
1959
New BTs -12" Maple bears S.42°W., 24.0 ft. scribed S20 CSBT
Rescribe 24" Laurel S.15½°E., 26.7 ft. S21 T24S R6W
CS BT.
Drive 6" Boat spike in center 40" Fir stump, bears
N.83°E., 58.0 ft., not scribed.
Chiseled 3" cross and "B.O.# on North face 3'x5'x5'
sandstone, bears S.70°W., 13.3 ft.

BLM resurvey by C. Albert White and Norman McDonald,
Cadastral Surveyors, under Group #244, surveyed June 1963
(DCSO records Vol. 32 Page(s) 13309-10)

The sec. cor., perpetuated by Byron in 1959, with an iron
post, 1" dia., protruding 12" above ground, firmly set with
DCSO 1959 brass cap
from which the remaining original bearing trees
A Madrone 28" dia., bears S.13°W., 41 lks. dist., mkd.
with an old blaze. Re-marked by Byron T24S R6W S21 CS
BT in the bark, beside the old blaze. (rec. brg. &
dist., S.15½°E., 39 lks.)
A burned out Fir stump 36" dia., bears N.82½°W., 60 lks.
dist., no marks remaining.
and bearing trees marked by Byron:
A sawed Fir stump 34" dia., bears N.82½°E., 89 lks. dist.,
with a steel spike driven into the center of the stump.
A Maple 13" dia., bears S.44¼°W., 37 lks. dist., mkd. S20
CS BT, on an open blaze.
and a bearing object mkd. by Byron,
A sandstone outcropping, 5 x 5 x 3 ft. above ground, bears
S.70°W., 20 lks. dist., mkd. BX0 on N. face.
No other trees available.

Mark Smalley - For: Roseburg Resources - 8/1998 - M 129-12

Found - 1959 county brass cap on iron pipe.
Rusted off 1" iron pipe N.10°E., 1.6'.
28" Madrone, S.15°E., (S.13°W.) 27.1'. Healed Orig.
34" Fir stump, N.82½°E., 58.7', rotten.
13" Maple, S.44½°W., 24.4', healed.
5x5x3' Sandstone outcropping S.70°W., 13.2', marked
"B 0 +"
Scribed- 11" Fir, N.34°E., 9.0', "S 16 BT"

continued next page

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

Alias	Description

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2963, surveyed Jan/April 2020- (DCSO records Vol. 59 Page(s) 23974-5)

The cor. of secs. 16, 17, 20 and 21, reported by White and McDonald in 1963; perpetuated by Smalley, in 1998; monumented with an iron post, 1¼" dia., firmly set projecting 15" above ground, with a brass cap (properly) mkd.

from which the accessories reported by White and McDonald

A decayed fir stump, 34" dia., bears N.82½°E., 58.7 ft., with a steel spike driven into the center of the stump.

A hollowed madrone, 33" dia., bears S.13°W., 27.1 ft., with a healed blaze. (Original)

A maple, 23" dia., bears S.44¼°W., 24.4 ft., with a healed blaze.

A sandstone outcropping, 5x5x3 ft. above ground, bears S.70°W., 13.2 ft., mkd. BX0 on N. face.

and the remains of a bearing tree mkd. by Smalley

A roothole bears N.37½°E., 10.1 ft., alongside of which is a down fir, 16" dia. with a healed blaze.

and new bearing trees

A fir, 22" dia., bears N.15½°E., 46.4 ft., mkd. T24S R6W S16 BT.

A fir, 21" dia., bears N.29¼°W., 36.7 ft., mkd. T24S R6W S17 BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.

From this cor., a point established, established by person(s) unknown for unknown purpose, reported by Smalley, and was not utilized for control in this survey, bears N.13°18'02"W. 1.60 ft., monumented with an iron pipe, 1" dia., firmly set, projecting 3" above ground.