

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3168)

Set Fir post 4 ft. long, 4" sq., 14" in the ground for ¼ sec. cor. mkd. ¼ S on West side, from which
A Fir 11" dia., bears N.15°20'E., 45 lks. mkd. ¼ S BT.
A Fir 12" dia., bears N.47°25'W., 78 lks. mkd. ¼ S BT.

BLM resurvey by C. Albert White and Norman J. McDonald, Cadastral Surveyor, under Group #(?), surveyed June 1963 (DCSO records Vol. 32 Page(s) 13310-11)

Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

 ¼
 S 17 | S 16
 T 24 | R 6 W
 1963

from which

A Fir 15" dia., bears S.57°E., 310 lks. mkd. ¼ S16 BT.
A Fir 30" dia., bears N.45°W., 195 lks. mkd. ¼ S17 BT.

Mark Smalley - For: Roseburg Resources - 8/1998 - M 129-12

Found - 1963 Cadastral brass cap on iron pipe.
19" Fir, bears S.57°E., 204.6', healed.
30" Fir, bears N.45°W., 128.7', snag healed.

Scribed- 16" Fir, S.67°W., 14.9', "¼ S BT"
11" Fir, N.39°W., 22.3', "¼ S BT"
15" Fir, North 17.1', "¼ S BT"
9" Fir, S.26°E., 29.7', "¼ S BT"

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2963, surveyed Jan/April 2020- (DCSO records Vol. 59 Page(s) 23975-6)

The ¼ sec cor, of secs. 16 & 17, reported by White & McDonald in 1963; and perpetuated by Smalley, in 1998, monumented with an iron post 2½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd.

from which the remains of the BTs reported by White & McDonald
A fir, 23" dia bears S.57°E., 201.8 ft., with a healed blaze. (Record, 204.6 ft.)

A decayed fir snag, 30" dia., bears N.45°W., 123.4 ft., with a healed blaze. (Record, 128.7 ft.) Cont.

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the bearing trees mkd. by Smalley
A fir, 15" dia., bears S.28¼°E., 30.0 ft., with a healed blaze.
A fir, 21" dia., bears S.68°W., 14.4 ft., with a healed blaze.
A fir, 16" dia., bears N.39°W., 22.1 ft., with a healed blaze.
A fir, 20" dia., bears N.1°W., 17.2 ft., with a healed blaze.