

PRIMARY CORNER DESCRIPTION Sec Cor for 8, 9, 16 and 17

Alias	Description

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3168)

Set Cedar post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 8, 9, 16 and 17, mkd. T24S S9 on NE.; R6W S16 on SE.; S17 on SW.; and S8 on NW. faces, with 4 notches on the South and 4 notches on the E. edges, from which
A Fir 50" dia., bears N.76°E., 52 lks. dist. mkd. T24S R6W S9 BT.
A Fir 54" dia., bears S.79°30'E., 158 lks. dist., mkd. T24S R6W S16 BT.
A Cedar 40" dia., bears S.72°30'W., 32 lks. dist., mkd. T24S R6W S17 BT.
A Fir 36" dia., bears N.14°30'W., 33 lks. dist., mkd. T24S R6W S8 BT.

BLM resurvey by C. Albert White and Norman McDonald, Cadastral Surveyors, under Group #(?), surveyed June 1963 (DCSO records Vol. 32 Page(s) 13311)

The Sec. cor., determined from original bearing trees:
A rotted Fir snag 52" dia., bears N.74°E., 51 lks. dist. with no marks remaining. (Record bearing and dist., N.76°E., 51 lks.)
A Fir 55" dia., blown down, bears S.79½°E., 158 lks. dist. lying face down, no marks visible.
A Cedar snag 35" dia., bears S.72½°W., 31 lks. dist., blaze rotted, no marks remaining. (Rec. dist. 32 lks.)
A Fir 54" dia., blown down, bears N.14½°W., 33 lks. dist., mkd. with portions of illegible bark scribing and old cruiser marks.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 24	S R 6 W
S 8	S 9
S 17	S 16

1963

from which new bearing trees:
A Hemlock 10" dia., bears N.35½°E., 23 lks. dist., mkd. T24S R6W S9 BT.
A Cedar 12" dia., bears S.80¼°E., 92 lks. dist., mkd. T24S R6W S13 BT.
A Fir 25" dia., bears S.30°W., 32 lks. dist., mkd. T24S R6W S17 BT.
A Hemlock 12" dia., bears N.74 3/4°W., 23 lks. dist., mkd. T24S R6W S8 BT.

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Mark Smalley - For: Roseburg Resources - 8/1998 - M 129-12

Found - 1963 Cadastral brass cap on iron pipe.
26" Hemlock, N.35½°E., 16.2'.
12" Cedar, S.80¼°E., 60.7'.
25" Fir, S.30°W., 21.1'.
12" Hemlock, N.74 3/4°W., 16.2'., down dead.
Scribed- 8" Fir, S.77°E., 38.8', "S16 BT"
8" Fir, S.18°W., 24.3', "S17 BT"
10" Fir, S.68°W., 25.2', "S17 BT"

Ron Rice - Josh Reed - 7/8/2010 - C.S. File 65/69-43

Found - 3¼" BLM brass cap dated 1963 with the following accessories:
30" Hemlock bears N.35½°E., 16.2' - healed face.
14" D.Fir bears S.68°W., 25.2' - healed face.
11" D.Fir bears S.18°W., 24.3' - healed face.
New - 14" D.Fir bears S.85°E., 45.6' - blazed, scribed "T24S R6W S16 BT"
Note - Corner has steel post adjacent to it. All BTs have red painted bands & yellow tag.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2963, surveyed Jan/April 2020- (DCSO records Vol. 59 Page(s) 23976-7)

The cor. of secs. 8, 9, 16 & 17, reported by White & McDonald in 1963; perpetuated by Smalley, in 1998; and subsequently perpetuated by Rice, in 2010, monumented with an iron post, 2½" dia., firmly set, projecting 1" above ground with a brass cap (properly) mkd.
from which the remains of the BTs reported by White & McDonald
A hemlock, 31" dia., bears N.35½°E., 15.2 ft., with a healed blaze.
A decayed fir stump, size indeterminate, bears N.74°E., 33.7 ft., no marks visible. (Original)
and the bearing trees mkd. by Smalley
A fir, 11" dia., bears S.17¼°W., 23.2 ft., with a healed blaze.
A fir, 16" dia., bears S.69½°W., 24.2 ft., with a healed blaze.
and a bearing tree mkd. by Rice
A fir, 15" dia., bears S.84°E., 45.4 ft., with a healed blaze.
and a new bearing tree

continued next page

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A maple 12" dia., bears N.29½°W., 28.4 ft., mkd. T24S R6W
S8 BT.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at
the base right side-center & each monument established or
remonumented has a magnet deposited in a white plastic case
at the base of the stainless steel post. Alum. Angle iron
driven alongside each monument.
NAD 1983 (2011)
Latitude: 43°29'25.69" N. Longitude: 123°25'34.20" W.