

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3178)

Set a Cedar post, 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 4, 5, 8 and 9, mkd. T24S S4 on NE.; R6W S9 on SE.; S8 on SW.; and S5 on NW. faces with 5 notches on the S. and 4 notches on the E. edges, from which

- A Fir 36" dia., bears N.44°E., 35 lks. dist. mkd. T24S R6W S4 BT.
- A Maple 18" dia., bears S.29°50'E., 32 lks. dist. mkd. T24S R6W S9 BT.
- A Fir 20" dia., bears S.18°W., 56 lks. dist. mkd. T24S R6W S8 BT.
- A Cedar 4" dia., bears N.26°10'W., 15 lks. dist. mkd. T24S R6W S5 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; S.A. Bilow - April 28, 1958 - C.S. File 49/83-29

Found - Orig. 20" now 24" R.Fir S.18°W., 37.0 ft. open face, good scribing "BT". (now dead)
 Orig. 4" now 12" Cedar snag N.26°W., 9.9 ft. I open and find scribe marks.
 48" Fir stump that checks record dist. and bearing for NE orig. BT. I do not open.

Set Brass cap at cor. mkd: County Surveyors Office

T	24	S	R	6	W
		S	5	S	4
		S	8	S	9
					1958

New BTs -24" W.Fir bears N.70°W., 118.5 ft. scribed S5 T24S R6W CS BT.
 12" R.Fir bears S.44°W., 110.5 ft. scribed S8 T24S R6W CS BT.
 33" Cedar bears N.35°E., 180.0 ft. scribed S4 T24S R6W CS BT.
 No trees near in SE.

BLM resurvey by C. Albert White and Norman McDonald, Cadastral Surveyors, under Group #(?), surveyed June 1963 (DCSO records Vol. 32 Page(s) 13315)

The sec. cor., perpetuated by Byron in 1958, with an iron post, 1" dia., protruding 14" above ground, firmly set, with 1958 brass cap from which the remaining original bearing trees:
 (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A sawed Fir stump 50" dia., bears N.44°E., 35 lks. dist., mkd. with a healed blaze.
A Fir snag 27" dia., bears S.18°W., 56 lks. dist., mkd. BT on an opened blaze.
A Cedar snag 12" dia., bears N.26°10'W., 15 lks. dist., mkd. with an opened blaze.
and bearing trees mkd. by Byron:
A Fir 15" dia., bears S.44 3/4°W., 167 lks. dist., mkd. T24S R6W S8 CS BT, on an open blaze.
A Fir 26" dia., bears N.70°W., 180 lks. dist., mkd. T24S R6W S5 CS BT, on an open blaze.
and a new bearing tree,
A sawed Cedar stump 36" dia., bears S.75°E., 126 lks. dist. mkd. T24S R6W S9 BT.
No tree available in section 4 within limits

Survey by Howard Johnstone - For: Roseburg Lumber Co. - May 6, 1982 - M 92-17

Found - 1958 County BCIP.
12" Cedar snag bears N.26½°W., 9.9 ft. (orig.)
27" Fir stump bears S.18°W., 37.0 ft. scribed "BT" (orig.)
BTs found scribed and tagged - not of record:
6" Fir N.53°W., 9.9 ft.
4" Fir S.24°W., 3.3 ft.
4" Fir S.32°E., 9.9 ft.
5" Fir N.23½°E., 6.3 ft.

Jerry Estabrook - Bruce Webster - 2/21/2004 - C.S. File 65/49-14

Condition Report only
Found - 2½" brass cap on 1" iron pipe, 1.25 ft. above grade.
A sawed fir stump 50" dia., bears N.44°E., 23.1 ft, with rotten face & tag.
A stump height rotten fir snag 20" (27") bears S.18°W., 37.0 ft. with visible scribe "S8"
A cedar snag 12", bears N.26°10'W., 9.9 ft. with visible chop marks.
A Grand fir 36" (26") dia., bears N.70°W., 117.8 (118.5) ft., with both high & low healed faces & 3 tags.
A sawed Cedar stump 36" bears S.75°E., 83.2 ft., with tag, no visible scribe or blaze.
A 10" (6") dia., fir, bears N.53°W., 9.9 ft. with healed face & tag.

continued next page

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A 11" (4") dia., fir, bears S.24°W., 3.3 ft. with
healed face & tag.
A 11" (4") dia., fir, bears S.32°E., 9.9 ft. with
healed face & tag.
A 10" (5") dia., fir, bears N.23°30'E., 6.3 ft. with
healed face & tag.
Note - Distances to fd. BTs were measured with EDM at
approx. side center of root crown. Trees were red
band & face painted. Trees fd. with out tags have
new tags facing monument