

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3182)

Set a Fir post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on West face, from which
A Fir 7" dia., bears S.19°30'E., 7½ lks. mkd. ¼ S BT.
A Fir 9" dia., bears S.15°30'W., 9 lks. mkd. ¼ S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; S.A. Bilow - April 1958 - C.S. File 49/83-29

Found - Orig. 7", now dead, 10" Fir S.19½°E., 5.0 ft. Open face, good scribing "BT".
R.Fir now 22", has open face but badly burned, no scribing found.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 6 W
¼ S 5 | S 4
1958

New BTs -28" R.Fir bears S.24°W., 14.0 ft. scribed ¼ S5 CSBT
24" R.Fir bears N.67°E., 9.9 ft. scribed ¼ S4 CS BT

Fd. OK, May 6, 1982, H.Johnstone, M 92-17