

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 33; & 4, T25-6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 8 Page 3132)

Set ¼ sec. post, from which
A Y.Oak 12" dia. bears N.62°W., 24 lks. dist.
A Fir 14" dia. bears S.65°W., 21 lks. dist.

G.G. Stewart, Bartrum & Shook, Witnesses. March 27, 1922
Volume 3 Page 115

Reestablish corner midway between section corners.
Set Iron pipe for corner and marked:
30" Fir S.26°E., 12.4 ft.
48" Fir N.17°E., 50.0 ft.

Douglas Co. Surveyors Office - Milo Godfrey - Nov. 1962 -
C.S. File 49/123

Not found.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J.
Flause - 2/2/98 - C.S. File 64/79-13

From orig. cor. position (1853):

Found - 14" now 22" dia., tipped out of ground, D.Fir
stump we open and find scribing "4S", bears
S.65°W., 13.9 ft. from root hole. (Note:
scribing found 7" from center of tree). OBT
Orig. NW BT not found.

From 1922 proportioned corner (calculated from 1922 BTs):

I.P. from 1922 not found.
30" now 30" dia., 6 ft. high, D.Fir stump shows
evidence of being previously opened no scribing
found old red paint on stump and a badly rusted
unreadable metal tag. Rec "S.26°E., 12.4 ft."
48" now 48" dia., 2 ft. high D.Fir stump, shows
evidence of being previously opened no scribing
visible. Record "N.17°E., 50.0 ft."
Set - 2 3/8" dia., brass cap on a 1 3/8" O.D. by 32"
long iron pipe is set at a position determined
from found orig. BT. Protrudes 6" above ground
(Note: E-W old buried fence line found while
digging out hole.)

(Cont. next page)

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33; & 4 T25-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Calculated 1922 proportioned corner bears approx.,
N.88°W., 13.5 ft. from set BC/IP.
17" dia., Madrone double blazed and scribed "¼ S33
CS BT" bears N.43°W., 34.7 ft.
12" dia., D.Fir, double blazed and scribed "¼ S33
CS BT", bears N.4°W., 27.0 ft.
1922 SE BT, now stump, bears S.37°W., 14.5 ft. add
bark scribing "X BT". No live trees south.
13" dia., B.Oak, double blazed and scribed "¼ S33
CS BT", bears N.2°E., 44.6 ft.
See sketch in file.

Found OK by D. Edwards, Jan. 2000 - CS65/29-2