

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Robert Elder & Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO rec Vol 8 Pg 3154)

Set post ¼ sec. post, from which
 A Y.Oak, 18" dia., bears S.42°W., 51 lks.
 A Y.Oak, 14" dia., bears N.8°W., 85 lks.

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch 9/8/2014 - C.S. File 67/41-42

Found - From an unrecorded renewal (Stones commonly set for corners in this area from late 1800's & early 1900's):
 A 4x5x21" tall sandstone marked with an "X" on top, a "1/ S +" on the east side and illegible but obviously scribed in marks on west side is set plumb protruding 10" above ground.

From an unrecorded 1999 Les Roberts renewal:
 A 5/8" dia., iron rod with a yellow plastic cap mkd "ROBERTS SURVEY INC" is set plumb protruding 1" above ground on the west edge of the above fd stone.

All accessories are measured from "X" on fd stone. Possible evidence of one original BT: Near the record bearing and distance of the original SW tree is a shallow indistinct root-hole with rotted Oak root remnants.

From the unrecorded 1999 Les Roberts renewal, 2 BTs:
 A 9" dia., D.Fir with a fully healed double blaze; bears S.54°E., 29.5 ft. (record from fd BT tag is S.54°E., 30.0 ft.)

An 11" dia., D.Fir with a fully healed double blaze; bears N.34°W., 40.5 ft. (agrees with record from fd BT tag.)

Also probably from the 1999 renewal: A green and white painted steel fence post is set West 1.0 ft. from the fd stone and protrudes 4 ft above ground.

New - 12" dia., madrone scribed "¼ S21" "CS BT" on a double blaze; bears N.38°E., 17.9 ft.
 14" dia., madrone scribed "¼ S28 CS" "BT" on a double blaze; bears S.14°W., 22.4 ft.

Note - Monument is on gentle west slope approx. 270 ft. west of a ridge top and in an open woods of mostly madrone with some scattered fir.
 Mostly down E-W fence 8' north of mon (per sketch) Compass decl. 15½°E.