

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3170)

Set a Cedar post, 4 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor. mkd. 1/4 S on N. face, from which
A Fir 18" dia., bears South, 9 lks. dist., mkd. 1/4 S BT.
A Fir 12" dia., bears N.80°E., 4 lks. dist. mkd. 1/4 S BT.

BLM resurvey by C. Albert White and Norman McDonald, Cadastral Surveyors, under Group #(?), surveyed June 1963 (DCSO records Vol. 32 Page(s) 13313)

The 1/4 sec. cor., determined at record distance from the remains of the original bearing trees:

A sawed Fir stump 18" dia., bears East, 4 lks. dist., mkd. with a flat ace and old axe marks on an opened blaze. (Rec. bearing, N.80°E.)

A sawed Fir stump 30" dia., bears S.5°E., 9 lks. dist., with no marks remaining. (Rec. bearing, South)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

1/4 $\frac{S}{S} \frac{9}{16}$
T 24 S R 6 W
1963

from which new bearing tree and bearing object:

A sandstone outcropping 7 x 6 x 4 ft. above ground, bears N.37°W., 33 lks. dist. mkd. B X 0.

A sawed Fir stump 38" dia., bears S.69°W., 81 lks. dist., mkd. 1/4 S16 BT.

Mark Smalley - For: Roseburg Resources - 8/1998 - M 129-12

Found - 1963 Cadastral brass cap on iron pipe.

18" Fir stump East 2.6', Orig.

30" Fir stump S.5°E., 5.9', Orig.

38" Fir stump S.69°W., 53.5'.

7x6x4' Sandstone outcropping marked "B X 0", bears N.37°W., 21.8'. Also marked "E E B"

Scribed- 10" Fir, N.65°E., 37.3', "1/4 S BT"

12" Fir, S.81°W., 65.6', "1/4 S BT"

Fd as per M129-12 - July 2018 by D Edwards, M174-53

continued next page

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2963, surveyed Jan/April 2020- (DCSO records Vol. 59 Page(s) 23977-8)

The ¼ sec. cor. of secs. 9 and 16, reported by White and McDonald in 1963; and perpetuated by Smalley, in 1998, monumented with an iron post 2½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd. from which the remains of the bearing trees reported by White and McDonald

A decayed fir stump, 18" dia., bears E., 2.6 ft., no marks visible. (Original)

A decayed fir stump, 30" dia., bears S.5°E., 5.9 ft., no marks visible. (Original)

A decayed fir stump, 38" dia., bears S.69°W., 53.5 ft., no marks visible.

A sandstone outcropping, 7x6x4 ft. high, bears N.37½°W., 21.2 ft., mkd. BX0 and FFB directly below on SE face. (Record, N.37°W., 21.8 ft.)

and the bearing trees mkd. by Smalley

A fir, 20" dia., bears N.65¼°E., 37.3 ft., with a healed blaze.

A fir, 21" dia., bears S.78½°W., 65.5 ft., with a healed blaze.