

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec Cor for 15, 16, 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3150)

Set post, cor. to secs. 15, 16, 21 and 22, from which
A W.Oak 14" dia., bears N.53½°E., 434 lks. dist.
A Fir 11" dia., bears S.17°W., 132 lks. dist.
A Y.Oak 16" dia., bears S.75¼°E., 130 lks. dist.
A Y.Oak 11" dia., bears N.30°W., 591 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; S.A. Bilow, crew - Sept. 1958 - C.S. File 49/83-10

Found - Orig. 11" now 48" down Fir S.17°W., 87.1 ft. I open log section and find good scribing "1 S"
No trace of other BTs.

Set Brass cap at cor. mkd: County Surveyors Office

T 24 S R 6 W
S16 | S15
S21 | S22
1958

New BTs -8" W.Oak bears N.64½°E., 164.7 ft. scribed S15 T24S R6W CS BT.
26" Ash bears N.15°W., 166.0 ft. scribed S16 T24S R6W CS BT.
6" W.Oak bears S.32°E., 45.1 ft. scribed S22 CS BT.
15" R.Fir bears S.65°W., 188.3 ft. scribed S21 T24S R6W CS BT.

Cor. Fd. and used in BLM resurvey by Berry and Akin, Cadastral Surveyors in 1973-75 survey (DCSO records, Vol. 37 Page 15245)

Cor. Fd. and used in BLM resurvey by Wayne Rogers, Cadastral Surveyor in 1979 (DCSO records, Vol. 42 Pgs. 16489-90)

Fd. Ok by D. Edwards, 9/1997 - 1998-0062 A&B

Mark Smalley - For: Roseburg Resources - 8/1998 - M 129-12

Found - 1958 County brass cap on iron pipe.
11" W.Oak S.33½°E., 44.9', (rec. S.32°E., 45.1'.)
Scribed- 9" W.Oak, S.29°W., 73.3', "S 21 BT"
14" W.Oak, S.82°E., 76.8', "S 22 BT"

continued next page

Alias	Description

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch
- Feb. 21, 2014 - C.S. File 67/41-17

-
- Found - A 2½" dia., brass cap (properly mkd) on a 1" I.D. iron pipe set protruding 8" above ground. Evidence of NE & NW orig. BTs destroyed by rock quarry excavation.
 - A fir 11" dia., now a very rotted 48" dia., 2 ft. tall D.Fir stump with old blaze search, axe marks (no evidence of scribed log remains); bears S.17°W., 82.9 ft. (rec. S.17°W., 87.1 ft; could be a slope measurement) OBT
 - A Y.Oak 11" dia., now a large distinct root-hole agrees reasonably with orig. rec. of S.75¼°E., 85.8 ft. OBT
 - 1958 BT, NW Ash destroyed by quarry work.
 - An 8" W.Oak now a large shallow root-hole containing W.Oak root remains; bears N.64½°E., 164.7 ft. (as per rec) 1958
 - A 6" W.Oak now a 13" dia., W.Oak, no longer showing blaze evidence; bears S.33½°E., 44.9 ft. (as per 1998 renewal rec.) 1958
 - A 15" R.Fir now a very rotted 30" dia., 1 ft. tall D.Fir stump, which is opened to find the scribing "BT"; bears S.65°W., 188.3 ft. (as per rec.) 1958
 - A 9" W.Oak now a 14" dia., W.Oak with a fully healed single blaze; bears S.29°W. 73.3 ft (per rec) 1998
 - A 14" W.Oak (mis-identified species) now an 18" dia., B.Oak with a fully healed single blaze; bears S.82°E., 76.8 ft. (as per rec.) 1998
- New - Tagged and flagged fd. BTs
- Note - Monument is on flat pastureland 6.5 ft. north of small seasonal stream and approx. 170 ft. south from south edge of large quarry operation. Monument is near foot of young fir reprod. covered north slope.
Compass decl. 15½°E.

Brent Knapp - For: Aaron Swan - 12/2024 - M184-46 A&B

-
- Found - Brass Cap Prop Mkd.
 - 13" W. Oak S.33½°E., 44.9' with no visible blaze.
 - 14" W. Oak S.29°W., 73.3' with healed blaze.
 - 18" B. Oak S.82°E., 76.8' with healed blaze.
 - 48" Rotten Fir stump S.17°W., 82.9
 - New - 27" Forked Oak N.53°E. 183.5' scribed "T24S R6W S15 BT"