

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3150)

Set ¼ sec. post, from which
A Y.Oak 14" dia., bears S.48°W., 15 lks. dist.
A Y.Oak 10" dia., bears S.88°E., 65 lks. dist.

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, and Glenn Baughman, LS #536 under Group #'s 826 and 856, Surveyed Sept. 1973/Aug. 1975 (DCSO records Vol. 37 Page(s) 15246)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd:
1/4
S 16 S 15
T 24 S R 6 W
1973

from which
A Fir 11" dia., bears N.48½°E., 68 lks. dist., mkd. ¼ S15 BT.
A Fir 8" dia., bears S.56½°W., 90 lks. dist., mkd. ¼ S16 BT.

Cor. Fd. and used in BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, under Group #1623, surveyed Sept/Oct. 1991 (DCSO records Vol. 50 Page(s) 19231)

Mark Smalley - For: Roseburg Resources - 8/1998 - M 129-12

Found - 1973 Cadastral brass cap on iron pipe.
16" Fir, bears N.48½°E., 44.9', healed.
8" Fir, bears S.56½°W., 59.4', healed.
Scribed- 13" Fir, N.7°W., 9.1', "¼ S BT"
13" Fir, S.22°W., 34.0', "¼ S BT"