

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3171)

-----  
Set a Fir post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which  
A Fir 26" dia., bears N.40°E., 9 lks. dist., mkd. ¼ S BT.  
A Fir 32" dia., bears S.65°50'W., 131 lks. mkd. ¼ S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; S.A. Bilow - Aug. 1958 - C.S. File 49/83-16

-----  
Found - Orig. 26" now 40" R.Fir N.40°E., previously opened, shows good scribe "BT"  
Orig. 32" now 36" R.Fir S.65°50'W., 86.5 ft., shows good scars. I do not open.

Set Brass cap at cor. mkd: County Surveyors Office  
T 24 S R 6 W  
¼ S9|S10  
1958

New BTs -Rescribe orig. now 40" R.Fir N.40°E., 5.9 ft. "¼ S10 CS BT"  
14" R.Fir bears S.78°W., 45.0 ft. scribed "¼ S9 CS BT."

FD OK by Ken Hoffine, April 1996 - M 123-66

Found OK by K. DeGroot, June 2004 - M146-6

Fd as per M123-66, Set 6' steel post 2' north 7/2018 - by D. Edwards M174-53