

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3171)

Set a Fir post 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 3, 4, 9 and 10, mkd. T24S S3 on NE.; R6W S10 on SE.; S9 on SW.; and S4 on NW. faces, with 5 notches on the S. and 3 notches on the E. edges, from which

- A Fir 5" dia., bears N.88°40'E., 26 lks. dist., mkd. T24S R6W S3 BT.
- A Fir 7" dia., bears S.78°25'E., 97 lks. dist., mkd. T24S R6W S10 BT.
- A Fir 5" dia., bears S.6°W., 30 lks. dist., mkd. T24S R6W S9 BT.
- A Fir 40" dia., bears N.86°50'W., 75 lks. dist., mkd. T24S R6W S4 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Oct. 1969 - C.S. File 52/102-5

Found - Orig. 40" now 48" Fir, alive, N.86°50'W., 49.5 ft., bark scribe visible.
 Orig. SW and SE BTs, now sawed stumps.
 Orig. NE BT, now blow down.

Set Brass cap at cor. mkd: County Surveyors Office

T	24	S	R	6	W
S	4		S	3	
S	9		S	10	
1969					

New BTs -32" D.Fir S.36°W., 20.0 ft. mkd. T24S R6W S9 CS BT
 22" D.Fir N.50°W., 22.1 ft. mkd. T24S R6W S4 CS BT
 20" D.Fir N.15°E., 38.3 ft. mkd. T24S R6W S3 CS BT
 No trees available in section 10 due to logging.
 Good blazed line North, cutting line S. and E.

Fd. OK, May 6, 1982, H. Johnstone, M 92-17
 FD OK by Ken Hoffine, April 1996 - M 123-66

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2314, Surveyed July/Aug. 2010 - (DCSO records Vol. 58 Page(s) 22887)

The cor. of sees. 3, 4, 9, and 10 perpetuated by the Douglas County Surveyor's Office in 1969, monumented with an iron post, 1¼" dia., firmly set, projecting 13" above ground, with a brass cap (properly) mkd.
 from which the remains of the original bearing trees
 continued next page

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A roothole bears N.88 $\frac{3}{4}$ °E., 17.2 ft., downhill of which is a down, decayed fir snag, size indeterminate, with no marks visible. (Record, N.88°40'E.)

A sawed fir stump, 36" dia., bears S.78 $\frac{1}{2}$ °E., 64.0 ft., with scribe marks R6W S visible on an opened blaze. (Record, S.78°25'E.)

A sawed, decayed fir stump, 28" dia., bears S.6° W., 19.8 ft., with no marks visible on an open blaze.

A sawed fir stump, 47" dia., bears N.86 $\frac{3}{4}$ °W., 49.5 ft., with a healed blaze. (Record, N.86°50'W.)

and the remains of BTs mkd by the Douglas Co Surveyors Office

A fir, 35" dia., bears N.14°E., 38.0 ft., with a healed blaze.

A fir, 41" dia., bears S.37 $\frac{1}{4}$ °W., 20.2 ft., with scribe marks T24S R6W S9 CS BT visible on bark.

A sawed fir stump, 34" dia., bears N.50°W., 21.9 ft., with a healed blaze.

and new accessories

A fir, 15" dia., bears S.69°E., 38.7 ft., mkd. T24S R6W S10 BT.

A rebar, 30" long, 5/8" dia., driven 28" in the ground for a reference monument, bears N.41°37'12"W., 14.98 ft. with aluminum cap mkd. RM T24S R6W S4 15.0 FT. TO COR 2010 and an arrow pointing to the cor.

Corner is located 180 ft. S. of a creek, 2 ft. wide, course N.38°W.

Latitude 43°30'17.34" N Longitude 123°24'22.41" W
(NAD 1983 (CORS 96))