

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4; & 33 & 34, T23-6

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2388)

-----  
Set post cor. to secs. 3, 4, 33 and 34, from which  
A Fir 36" dia., bears N.44°E., 19 lks.  
A Fir 40" dia., bears S.3°E., 93 lks.  
A Fir 40" dia., bears S.71°W., 17 lks.  
A Fir 16" dia., bears N.35°W., 86 lks.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3176-77)

-----  
The Sec. Cor., post gone, bearing trees all down. Stump of one in place with marks. Two others uprooted but not decayed, as is also sight trees 36 lks. dist. East. Notches plainly visible. Reestablished same by setting a Yew post, 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 3, 4, 33 and 34, mkd. T23S S34 on NE.; T24S S3 on SE.; R6W S4 on SW.; and S33 on NW. faces, with 6 notches on the S. and 3 notches on the E. edges, from which

The stump of original bearing tree, 40" dia., bears S.71°W., 17 lks. dist. mkd. T24S R6W S4 BT.

Take new bearing trees as follows:

A Fir 62" dia., bears N.48°15'E., 69 lks. dist., mkd. T23S R6W S34 BT.

A Fir 5" dia., bears S.31°10'E., 48 lks. dist., mkd. T24S R6W S3 BT.

A Fir 4" dia., bears S.43°W., 13 lks. dist., mkd. T24S R6W S4 BT.

A Fir 5" dia., bears N.17°15'W., 25 lks. dist., mkd. T23S R6W S33 BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12645)

-----  
The Sec. cor., determined at record bearing and distance from one of the original bearing trees:

A Fir 48" dia., bears S71°W., 17 lks. dist., marks rotted off.

At the corner point

Set an iron post, 30" long, 2" dia., 20" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4; & 33 & 34, T23-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

T23SR6W  
S33\*S34  
S 4\*S 3  
T24S  
1957

from which

- A Fir 9" dia., bears N.51½°E., 49½ lks. dist., mkd. T24S R6W S34 BT.
- A Fir 22" dia., bears S.32½°E., 47 lks. dist., mkd. T24S R6W S3 BT.
- A Fir 21" dia., bears S.49°W., 58 lks. dist., mkd. T24S R6W S4 BT.

No bearing tree available in sec. 33.

Fd. OK, May 6, 1982, H. Johnstone, M 92-17

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19448)

-----

At the cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above a collar of stone (with T iron alongside), with brass cap mkd.

T 23 S R 6 W  
S33 \* S34  
S4 \* S3  
T 24 S R 6 W  
1957

from which remains of an original bearing tree

- A fir stump, 48 ins. diam., bears S. 71° W., 17 lks. dist., with scribe marks R6W T24 visible on open blaze.

and bearing trees mkd. by Gould, Gawron, and Eggen

- A fir, 12 ins. diam., bears N. 51½° E., 49½ lks. dist., with healed blaze.
- A fir, 28 ins. diam., bears S. 32½° E., 47 lks. dist., with healed blaze.
- A fir, 25 ins. diam., bears S. 49° W., 58 lks. dist., with healed blaze.

and a bearing tree not of record

- A fir, 30 ins. diam., bears N. 13° W., 26 lks. dist., with healed blaze.

continued next page

2

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4; & 33 & 34, T23-6

Alias	Description

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2308, Surveyed April/July 2010 - (DCSO records Vol. 57 Page(s) 22833)

-----  
The cor. of secs. 3, 4, 33, & 34, on the S. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 5" above a mound of stone, 2 ft dia., 1 ft high (alongside of which is a "T" shaped iron rod, ¾" dia., firmly set, projecting 7" above the mound of stone, with a brass washer mkd. WILFORD N. HAINES SURVEY 239 DRAIN, ORE., with a tack in center), with a brass cap (properly) mkd.

from which the remains of the original bearing trees

A roothole bears S.3°E., 61.4 ft., downhill of which is a down, decayed fir snag, size indeterminate, with no marks visible.

A decayed fir stump, 48" dia., bears S.71°W., 11.2 ft., with scribe marks R6W T24 S4 visible on an open blaze. and the remains of bearing trees mkd. by Whipple

A sawed, decayed fir stump, 55" dia., bears N.48¼°E., 45.5 ft., with a healed blaze. (Record, 62" dia..)

A roothole bears S.31¼°E., 31.7 ft., downhill of which is an uprooted fir snag, 29" dia., with a healed blaze. (Not identified and rescribed as new by Gould, Gawron, and Eggen in 1943-57.)

A decayed fir stump, 3" dia., bears S.43°W., 8.6 ft., with scribe mark T visible on an open, pitched blaze.

A fir, 35" dia., bears N.17¼°W., 16.5 ft., with a healed double blaze. (Misidentified as a bearing tree not of record by Rogers, et al, in 1986-95.)

and the remains of a BT mkd. by Gould, Gawron, and Eggen, reported by Rogers, et al, in 1986-95

A fir, 13" dia., bears N.51½°E., 32.7 ft., with a healed blaze.

and new bearing trees

A fir, 25" dia., bears S.72¼°E., 45.1 ft., mkd. T24S R6W S3 BT.

A cedar, 18" dia., bears S.54½°W., 28.8 ft., mkd. T24S R6W S4 BT.

Corner is located 90 ft. W. of Yellow Creek, 17 ft. wide, course S.20°E.

FD & used on BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2314, Surveyed July/Aug. 2010 - (DCSO records Vol. 58 Page 22887)