

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 34; & 3, T25-6

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 8 Page 3131)

Set 1/4 sec. post, from which
A B.Oak 16" dia. bears N.20°W., 31 lks. dist.
A B.Oak 14" dia. bears S.41½°E., 195 lks. dist.

Bureau of Land Management Dependent Resurvey - June 1972
Stephen Albright; Jack Bowder - (DCSO records, Volume 36
Page 14998)

There is no remaining evidence of the original corner.
Set an iron post, 28" long 2½" dia. 24" in the ground, with
brass cap mkd:

T 24 S R 6 W
 S 34
1/4 S 3
 T 25 S
 1972

from which
A Madrone 7" dia. bears N.37½°E., 21 lks. dist. mkd.
1/4 S34 BT.
An Oak 10" dia. bears S.29°E., 151 lks. dist. mkd.
1/4 S3 BT.

Found OK June 1994 by K. DeGroot - M119-34.
Fd. OK by M. Heimburger, Nov. 2001 - M139-16
Fd. Ok by M Heimburger, 2/2013 - M164-60