

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 3; and 34, T23-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2388)

-----

Set ¼ sec. post, from which  
 A Fir 18" dia., bears N.57°W., 16 lks.  
 A Fir 20" dia., bears S.83°W., 57 lks.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12644-45)

-----

(39.98 chains)  
 Point for witness to the ¼ sec. cor. of secs. 3 and 34.  
 Set an iron post, 30" long, 2" dia., 18" in the ground and in a mound of stone, 3 ft. base, to top, with brass cap mkd:  
 W C  
 T23SR6W  
 ¼ S 34  
     S 3  
 T24S  
 1957

from which  
 A Fir 8" dia., bears N.1½°E., 28 lks. dist., mkd. XBT.  
 A Fir 8" dia., bears S.10¼°E., 17 lks. dist., mkd. XBT.

(40.09)  
 The ¼ sec. cor. of secs. 3 and 34, determined at record distance and bearing from the original bearing trees:  
 A Fir 40" dia., bears S.84°W., 71 lks. dist., with healed blaze.  
 A Fir 33" dia., bears N.57°W., 25 lks. dist., mkd. BT.  
 The point for cor. falls on the roots of a Fir, dead and down, where it is impracticable to establish a permanent monument.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2308, Surveyed April/July 2010 - (DCSO records Vol. 57 Page(s) 22832)

-----

The witness cor. to the ¼4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 5" above a mound of stone, 2 ft. dia., 1 ft. high, (alongside of which is a "T" shaped iron rod, 3/4" dia., firmly set, projecting 24 ins. above the mound of stone, with a brass washer mkd. WILFORD N. HAINES SURVEY 239 DRAIN, ORE., with a tack in center) with a brass cap (properly) mkd.

continued next page

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 3; and 34, T23-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which bearing trees mkd. by Gould, Gawron, and Eggen  
A fir, 13" dia., bears N.1½°E., 18.5 ft., with axe mark  
X visible and a healed blaze at base.

A fir, 12" dia., bears S.10¼°E., 11.2 ft., with axe mark  
X visible and a healed blaze at base.

The true point for the ¼ sec. cor. of secs. 3 and 34, on the  
S. bdy. of the Tp., in a location impracticable to establish  
a permanent monument, determined at Elder and Gile's record  
bearings and distances from the original bearing trees

A fir, 43" dia., bears S.83°W., 37.6 ft., with a hollow  
blaze. (Gould, Gawron, and Eggen's record is S.84°W.,  
46.9 ft.)

A fir, 39" dia., bears N.37°W., 10.6 ft., with illegible  
scribe marks visible on a partially healed blaze.  
(Gould, Gawron, and Eggen's record is N.57°W., 16.5  
ft.)

Note: Bearings and dists. from the true point for the  
original ¼ sec. cor. of secs. 3 and 34 to the original BTs  
were erroneously reported by Gould, Gawron, and Eggen in  
1943-57 as bearings and dists. from the witness cor. to the  
original bearing trees.