

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors,
under Contract #31 dated April 7, 1853 (DCSO records Vol. 8
Page(s) 3141)

Set ¼ sec. post, from which
A W.Oak 12" dia., bears N.72½°E., 221 lks. dist.
A Y.Oak 16" dia., bears N.25°W., 367 lks. dist.

Survey by G.G. Stewart, DCS - Wit: Leatherwood; Baird;
Bartrum and McHugil - March 27, 1922 - Vol. 3 Page 115

Reset from one O.B.T. Other tree gone.
Set rock for corner.
16" B.Oak N.25°W., 242 ft.
18" Fir NE (?) 53.0 ft

Survey by Romano E. Ware - For: Gary Barnett and Roseburg
Lumber - April 1979 - M 70-59

Found - Wood hub.
26" Fir stump with scribing bears N.52°30'E., 53.0
ft.
Set 5/8" Iron rod.
New BT - 12" Oak bears S.60°E., 44.0 ft. scribed ¼ S35 BT.

Fd. OK, Sept. 1993, R.Dolan, C.S. File 63/97-3

Mark Smalley - For: Roseburg Resources - 7/2002 - C.S. File
65/44-9

Found - 5/8" IR - good
26" Fir stump N.52°30'E., 53.0 ft. - rotted, no
marks remaining.
16" W.Oak S.60°E., 44.0 ft. - Good
New - 23" D.Fir bears due East 45.9' scribed "¼ S35 BT"
9" D.Fir bears S.16°E., 49.2' scribed "¼ S35 BT"
6" D.Fir bears N.85°W., 35.7' scribed "¼ S34 BT"
Compass decl. 18°E.