

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors,
under Contract #31 dated April 7, 1853 (DCSO records Vol. 8
Page(s) 3141)

Set post cor. to secs. 26, 27, 34 and 35, from which
A Y.Oak 30" dia., bears N.68°W., 47 lks. dist.
A Y.Oak 15" dia., bears N.1½°E., 40 lks. dist.
A Y.Oak 16" dia., bears S.68½°E., 87 lks. dist.
A Y.Oak 18" dia., bears S.37½°W., 313 lks. dist.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones,
W. Penley, crew - Sept. 12, 1969 - C.S. File 52/102-4

Found - 16" now 40" B.Oak S.64°E., (Rec. S.68½°E.) 57.4 ft.,
shows faint scar.
15" B.Oak, now dead, N.13°E., (Rec. N.1°E.) 26.4
ft., previously open, found reverse scribe "BT"
30" B.Oak now rotten stump, N.68°W., 31.0 ft., no
marks found.
SW BT, down and rotten, hits fair for bearing
S.37½°W., 206.6ft.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 6 W
S 27 | S 26
S 34 | S 35
1969

New BTs -6" W.Oak S.59½°E., 21.3 ft. mkd. T24S R6W S35 CS BT
11" D.Fir N.20°E., 38.1 ft. mkd. T24S R6W S26 CS BT
12" Laurel N.43°W., 38.3 ft. mkd T24S R6W S27 CS BT
18" Laurel S.79°W., 23.5 ft. mkd T24S R6W S34 CS BT
Corner lies 1.0 ft. S. of old fence corner, running N-E & W.

Fd. B.C., 4 orig. BTs and 4 BTs mkd. by Powell, by Wayne
Rogers, Cadastral Surveyor, BLM survey under Group #969,
surveyed April/May 1979 (DCSO Records, Vol. 42 Pgs.16483-84)

Fd. OK, July 1992, M. Heimbürger, M 112-50
Fd. Ok by D. Edwards, 10/2005 - M148-79