

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3142)

-----  
Set ¼ sec. post, from which  
A Y.Oak 20" dia., bears S.44°W., 19 lks. dist.  
A Laurel 17" dia., bears S.48°E., 39 lks. dist.

Floyd J Cole, Deputy - M.F. Riggs; F Adams; H Larkin Witnesses - June 12, 1915 - Field Book 37 Pg 49 & Vol. 2 Pg 270

-----  
Renew corner from original trees. Find Laurel standing and chop marks on stump of Oak BT.  
Set rock 6 x 14 x 16 inches mkd. + from which  
A B.Oak 12" dia., S.3°W., 143 lks.

Searched for, not found, DCSO J. Powell, Sept. 1970, C.S. File 52/102-19 - Found fence cor. - possible place for orig. laurel no trace of other BTs or stone - stone gone because of old skid rd.

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, under Group #969, surveyed April/May 1979 (DCSO records Vol. 42 Page(s) 16485)

-----  
The ¼ sec. cor., perpetuated and recorded by Germond in 1908 (?), determined at record bearing and distance from the remains of the original bearing trees:

A Laurel 36" dia., bears S.48°E., 39 lks. dist., with axe marks visible on decayed blaze.  
A root hole, bears S.44°W., 19 lks. dist.  
and the remains of a bearing tree mkd. by Germond  
A root hole bears S.3°W., 143 lks. dist., with a down Oak alongside, 20" dia., with axe marks visible on decayed blaze.

At the corner point  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 24 S R 6 W  
1/4  
S 27 | S 26  
1979

from which new bearing trees  
A Fir 12" dia., bears S.65°E., 28 lks., mkd. ¼ S26 BT.  
A Fir 18" dia., bears S.73°W., 66 lks., mkd. ¼ S27 BT.

Fd. Ok by D. Edwards, 10/2005 - M148-79