

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3142)

-----  
Set post cor. to secs. 22, 23, 26 and 27, from which  
A Y.Oak 24" dia., bears N.78°W., 777 lks. dist.  
A W.Oak 12" dia., bears S.48°W., 400 lks. dist.  
Made trench, no other trees convenient.

Floyd J. Cole, Deputy - Wit: M.F. Riggs; F. Adams; H.Larkin - June 12, 1915 - Field Book 37 Page 50 & Vol. 2 Page 270

-----  
No evidence of BT. Set a rock 8" x 16" x 20" for corner, from which  
An Ash 14" N.17°E., 203 lks.  
An Ash 9" N.5°W., 240 lks.  
An Ash 10" S.82½°E., 134 lks.  
Maple 20" S.20½°W., 424 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Sept. 10, 1956 - C.S. File 47/135

-----  
Found - Chisled + on 8" x 12" stone under E-W fence.  
10" Ash now 30", S.82½°E., 88.5 ft.  
Found scribe marks on stump. Other BTs gone.  
Set an iron pipe with brass cap at corner point alongside stone and mkd: County Surveyors Office  
T 24 S R 6 W  
22|23  
27|26  
1956

Blazed and scribed new trees:  
6" Ash N.9°30'E., 95.4 ft. mkd. S23 T24S R6W CS BT  
8" W.Oak N.87½°E., 40.8 ft. mkd. S23 T24S R6W CS BT  
No other trees near.

-----  
(Above corner to secs. 22, 23, 26 and 27 reset by Floyd C. Frear on April 27, 1956 from road survey made by himself in Feb. 1919. He found same apparent stone with X on top. See C.S. File 47/137)

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, under Group #969, surveyed April/May 1979 (DCSO records Vol. 42 Page(s) 16486)

-----  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

The Sec. Cor., reestablished by proportionate measurement by Cole in 1915, and perpetuated and recorded by Byron in 1956, and is accepted as the best available evidence of the position of the original corner, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground, with a 1956 DCSO brass cap.

from which the remains of a bearing tree mkd. by Cole:

A root hole bears S.82½°E., 134 lks. dist.

and the remains of bearing trees mkd. by Byron

An Ash 15" dia., bears N.9½°E., 145 lks. dist., with scribe marks 6W visible on partially healed double blaze.

A sawed Oak stump 18" dia., bears N.87½°E., 67 lks. dist., no marks visible.

and new bearing trees

An Ash 7" dia., bears S.65°E., 463 lks. dist., mkd. X BT.

A Fir 14" dia., bears S.30°W., 352 lks. dist., mkd. T24S R6W S27 BT.

An Ash 20" dia., bears N.6°W., 241 lks. dist., mkd. T24S R6W S22 BT.

Corner is located in woven wire fence, extending E and W.

Douglas Co. Surveyors Office - Stephen Flause and Bill Stewart, crew - Aug. 18, 1980 - C.S. File 61/11-17

-----  
CONDITION REPORT ONLY

Found - An 8"x16"x20" stone protrudes approx. 2" from ground and has a possible "+" mark near a chipped corner on its South edge.

A 5/8" I.R. protrudes 14' from ground and is set on the East edge of the stone (C.S. 47/137)

A 1956 DCSO brass cap, properly mkd., on a 1" x 39" I.P. protrudes 3" from ground and is on the North edge of the stone.

A search for original BTs is made but none are found. No evidence of any trees from 1915 is found.

A 6" Ash now 15" bears N.09°E., 95.4 ft. from the center of the above found monuments (all following bearing and distances are similarly measured), (record is N.9°30'E., 95.4 ft.) This tree has a double blaze, no scribing visible.

An 8" W.Oak now a 15" W.Oak stump, 1 ft. tall, bears N.87½°E., 40.8 ft. No evidence of blaze found.

Monuments found are located in an E-W fenceline.

Also found - Unrecorded BLM accessories: (unrecorded at the time of this visit)

(Cont. Next Page)

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A 5" Ash bears S.65½°E., 305.2 ft. (1979 BLM tag reads reverse bearing and dist. N.65°W., 463 lks.) Tree is bark scribed "X BT"  
An 18" D.Fir bears S.30°W., 232.2 ft. (1979 BLM tag reads reverse bearing and dist. N.30°E., 352 lks.) Tree is scribed T24S R6W S27 bT on a single blaze.  
A triple trunk Ash with a 31" DBH, on the scribed double trunk bears N.06°W., 159.0 ft. (1979 BLM reverse bearing and dist. S.06°E., 241 lks.) scribed T24S R6W S22 BT on a single blaze.

Fd. OK, July 1992, M. Heimburger, M 112-50

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, under Group #1623, surveyed Sept/Oct. 1991 (DCSO records Vol. 50 Page(s) 19229)  
-----  
The cor. of secs. 22, 23, 26 and 27, identical with the Bureau of Land Management Geodetic Control Station No. 71013 "SWAN" bears S.26°26'46"E., 89.323 chs. dist. from the 1/4 sec. cor. for secs. 15 and 22. (Mean bearing and sea level distance). The geographic position (NAD 1927) of the station, determined with Magnavox MX-1502 Receivers in 1987, is latitude 43°27'41.185" N., longitude 123°23'06.531" W. The station is monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T24S R6W S22 S23 S26 S27 1956.

Fd. Ok by Carl Sweeden, 5/2007 - 2007-0106

Brent Knapp - For: Aaron Swan - 12/2024 - M184-46 A&B  
-----  
Found - Co. Surveyor brass cap (properly mkd)  
18" Ash N.9°E., 95.4' with healed blaze.  
9" Ash S. 66°E., 305.5' with healed blaze.  
36" Ash N.6°W., 159.0' with healed blaze.  
New - 5/8" IR S.71°W., 186.2' set fence post next to rod  
5/8" IR S.18°W., 159.8' set fence post next to rod