

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3143-44)

Set ¼ sec. post, from which
 A W.Oak 30" dia., bears S.89°W., 775 lks. dist.
 A W.Oak 28" dia., bears S.16½°E., 292 lks. dist.

Briggs - 1888 - Vol. 1 Page 117

Set Post by old BT.

Survey for M.T. Riggs, etal - June 1915 _ Vol. 2 Page 270 and Field Book 37 Page 49

A Large fence post which G.W. Copper says is set in the identical place that Germond set the ¼ corner when the stump of the tree S.16½°E., 292 lks. The other tree was down at that time. I check by place indicated where Haines says he took out a stump and find the fence post correct as near as I can tell.

Looked for, not found by DCSO

Brent Knapp - For: Aaron Swan - 12/2024 - M184-46 A&B

Set - 5/8"x30" iron rod W/YPC mkd: "I.E. ENGINEERING"
New - 5/8" iron rod S.79°45'E., 104.8'
 5/8" iron rod S.64°30'E., 53.8'
 5/8" iron rod N.59°W., 27.9'
 58" Oak S.86°E., 173.1' scribed "¼ S23 BT"