

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3144)

-----  
Set post cor. to secs. 14, 15, 22 and 23, from which  
A W.Oak 15" dia., bears S.7 3/4°E., 306 lks. dist.  
A W.Oak 16" dia., bears S.72°W., 15 lks. dist.  
A W.Oak 20" dia., bears N.45°W., 47 lks. dist.  
A W.Oak 30" dia., bears N.57°E., 31 lks. dist.

H.L. Eppstein, Co. Surveyor - Wit: P.H. Wolford; Geo Spaur; Chs. Cooper - Jan. 16, 1926 (No record source, see "old" corner book, page 48)

-----  
Set Oak stake. Mark BT.  
A W.Oak 40", S.7 3/4°E., 306 lks. Old tree  
A W.Oak 30", N.45°W., 47 lks. Old tree  
A W.Oak 30", S.48°W., 21 lks. New tree  
A W.Oak 36", N.57°E., 31 lks. Old tree, remarked.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; S.A. Bilow, crew - Sept. 2, 1958 - C.S. File 49/83-21

-----  
Found - Orig. 15" now 46" W.Oak, shows good scars, I do not open.  
Orig. 20" now 36" W.Oak N.45°W., 31.0 ft. I do not open.  
Orig. 30" now 40" W.Oak N.57°E., 20.5 ft. I open and find good scribe marks "BT". (Eppstein 1926)  
Eppstein 30" now 40" W.Oak, down, S.48°W., 13.9 ft.  
Find 1" drill steel at corner. I do not set brass cap.  
New BTs -14" W.Oak bears N.46°W., 10.6 ft. scribed S15 T24S R6W CS BT.  
6" W.Oak bears S.65°W., 25.5 ft. scribed S22 T24S R6W CS BT.  
14" R.Fir bears N.5°E., 37.8 ft. scribed T24S R6W S14 CS BT.  
8" W.Oak bears S.81°E., 37.3 ft. scribed T24S R6W S23 CS BT.

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, and Glenn Baughman, LS #536 under Group #'s 826 and 856, Surveyed Sept. 1973/Aug. 1975 (DCSO records Vol. 37 Page(s) 15244)

-----  
(Cont. Next Page)

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

The sec. cor., determined at record bearing and distance from the remains of the original bearing trees:

A W.Oak 30" dia., bears N.57°E., 31 lks. dist., with scribe marks BT visible on open blaze.

A W.Oak 43" dia., bears S.7 3/4°E., 306 lks. dist., with healed blaze.

A W.Oak 36" dia., bears N.45°W., 47 lks. dist., with healed blaze.

and bearing trees mkd. by Byron in 1958:

A Fir 19" dia., bears N.5°E., 57 lks. dist., with healed blaze.

A W.Oak 11" dia., bears S.81°E., 55½ lks. dist., with healed blaze.

A W.Oak 8" dia., bears S.65°W., 40 lks. dist., with healed blaze.

A W.Oak 14" dia., bears N.46°W., 16 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 24 S R 6 W  
S 15 | S 14  
S 22 | S 23  
1973

Fd. and used in BLM resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1623, surveyed Sept/Oct. 1991 (DCS0 records, Vol. 50 Page 19226

Fd. BC & 6 BTs by C. Sweeden, 2/2012 - M163-27  
Fd as per M163-27 5/2018 (filed 6/2021) by M Schulze, M179-44

Brent Knapp - For: Aaron Swan - 12/2024 - M184-46 A&B

-----  
Found - County surveyor brass cap (properly mkd)  
15" W.Oak S.33½°E., 44.9' with no scar.  
16" W.Oak S.29°W., 73.3' with healed blaze  
21" B.Oak S.82°E., 76.8' with healed blaze  
48" Fir stump, rotten, S.17°W., 82.9'  
New - 27" Forked Oak N.53°E., 183.5', scribed "T24S R6W S15 BT".