

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

<p>GLO survey by William R Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO recs Vol 8 Pg) 3175)</p> <p>-----</p> <p>Set a Chestnut post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on W. side, from which A Fir 34" dia., bears S.48°30'W., 30 lks. mkd. ¼ S BT. A Fir 22" dia., bears S.52°20'E., 19 lks. mkd. ¼ S BT.</p>
<p>Survey by Wilford N. Haines - For: E.G. Whipple and Harold Woolley - Sept. 1957 - M 5-52</p> <p>-----</p> <p>Found - 34" Fir S.48°30'W., 30 lks. 22" Fir S.52°20'E., 19 lks. Set 1" x 1" x 36" Iron T rod with brass cap for ¼ corner inscribed "Wilford N. Haines, Drain, Oregon, #239 Survey Pt"</p>
<p>Fd. OK, DCSO, J.Byron, Aug. 1958, C.S. File 49/83-15</p>
<p>Douglas Co. Surveyors Office - Gary E. Commons, Peter L. Earle, Crew - March 31, 1975 - C.S. File 57/21-4</p> <p>-----</p> <p>Found - Haines "T" iron with washer buried in ground. 34" Fir now 42", S.48½°W., 19.8 ft. Haines washer attached. 22" Fir now still 22" snag, S.52°20'E., 12.5 ft. with Haines washer attached, scribe has been opened previously. Set 1½" x 30" I.Pipe with Brass cap at cor. 28" in ground, mkd: County Surveyors Office T 24 S 1/4 S3 S2 R6W 1975 New BT - 12" Hemlock N.71°E., 157.0 ft. scribed ¼ S2 CS BT</p>
<p>Ken Hoffine - For: Lone Rock Timber Co. - Aug. 2016 - C.S. File 65/93-32</p> <p>-----</p> <p>Found - Co. cap with Haines T-iron alongside 50" D.Fir bears S.49¼°W., 19.9 ft (Rec. S.48°30'W., 19.8 ft.) Healed face and tag. Rotten D.Fir stump bears S.52½°E., 12.3 ft. (Rec. S.52°20'E., 12.54 ft.) visible scribing. Record 12" Hemlock Per CS 57/21 Was not looked for. New - 36" D.Fir bears N.45¼°W., 44.4 ft. we scribe T24S R6W S3 ¼ BT and tag tree continued next page</p>

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

15" D.Fir bears N.69 $\frac{3}{4}$ °E., 16.2 ft. we scribe T24S
R6W S2 $\frac{1}{4}$ BT and tag tree
21" D.Fir bears S.49 $\frac{1}{2}$ °E., 55.6 ft. we scribe T24S
R6W S2 $\frac{1}{4}$ BT and tag tree
Beginning at the C $\frac{1}{4}$ corner of sec. 2 T24S R6W which is a "X"
carved in bedrock we ran a random traverse westerly to the
W $\frac{1}{4}$ of Sec 2 thence northerly to the NWSC of Section 2.
Rotated our traverse to the record from Haines Survey M5-52
from the C $\frac{1}{4}$ to the W $\frac{1}{4}$. We blazed, painted, tagged, and
flagged boundary lines as shown on sketch. Found County Cap
for quarter corner between sections 2 and 3, with Haines
T-Iron along side. Corner is located on flat bench with the
termination of East - West fence line approx 3 feet south of
corner.