

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 35

Alias	Description

Survey by Romanso E. Ware - For: Gary Barnett and Roseburg Lumber - April 1979 - M 70-59 ----- Set 5/8" Iron rod. BTs - 6" oak scribed C $\frac{1}{4}$ S35 BT bears S.74°E., 9.7 ft. 8" Oak bears N.26°E., 20.7 ft. scribed C $\frac{1}{4}$ S35 BT. Fence corner 20 ft. South. 5 ft. dia., Oak, 3 ft. South.
Mark Smalley - For: Roseburg Resources - 7/2002 - C.S. File 65/44-10 ----- Found - 5/8" iron rod - OK in down fence line 7" Oak snag with closed face bears S.74°E., 9.7 10" Oak stump - rotted, no marks remaining bears N.26°E., 20.7 Fence corner - okay - bears South, 20.0 48" Oak (rec. 5') - fair - bears South 3.0 New - 14" W.Oak bears S.49°E., 21.0 scribed "C $\frac{1}{4}$ S35 BT" 9" W.Oak bears S.69°W., 15.4 scribed "C $\frac{1}{4}$ S35 BT" Compass decl. 18°E.
Fd. Ok by K. DeGroot - 9/2007 - 2007-0129A&B Fd. Ok by K. DeGroot - 5/2012 - M164-27