

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias 041010 Description NNE Cor. Parker DLC #41
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors,
under Contract #31 dated April 7, 1853 (DCSO records Vol. 8
Page(s) 3142)

Set $\frac{1}{4}$ sec. post,
Drove charred stake and raised mound with trench and pits as
per instructions.
(The SW cor. of H. Pinkstone's claim bears S.33 $\frac{1}{2}$ °W., 569 lks.
dist.)

W.F. Briggs - For: Berrell, Burch and Sutherlin - Oct. 1891
-Vol. 1 Page 189

Set $\frac{1}{4}$ S post, marked $\frac{1}{4}$ S C 41 CS.

Survey by Mark Heimburger - For: W.D. Henry - July 6, 1992
M 112-50

Set a 2 $\frac{1}{2}$ " x 30" alum. pipe 28" in the ground with a 3 $\frac{1}{4}$ " alum.
cap mkd: T24S R6W
 $\frac{1}{4}$ $\frac{S\ 26}{S\ 35}$
RLS 2287
1992

from which
11" B.Oak bears N.7°W., 133.8 ft. scribed " $\frac{1}{4}$ S26 BT"
8" D.Fir bears S.87°E., 82.1 ft. scribed " $\frac{1}{4}$ S35 BT"
Old fence corner bears S.75°W., 27.5 ft.