

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3136)

Set post cor. to secs. 23, 24, 25 and 26, from which
A W.Oak 26" dia., bears S.50 1/6°W., 703 lks. dist.
A W.Oak 10" dia., bears S.10¼°E., 775 lks. dist.
Made trench, no trees near North of line.

F.C. Frear, Doug. Co. Surveyor - Wit: H.L. Eppstein; H.F. Crocker - Oct. 2, 1919 - C.S. File 1/1 and Field book 47 Pages 1-13

Re-established as per old BTs be setting a 6" x 12" x 3" sandstone, from which
A 36" W.Oak bears S.48°55'W., 7.03 chs. (OBT)
A 36" W.Oak bears S.11°25'E., 7.75 chs. (OBT)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone, crew - Oct. 23, 1962 - C.S. File 49/83-31

Found - Sandstone rock set in 1919.
Oak, dead and down, S.10¼°E., 511.5 ft. Had been opened years ago. Nearly all rotted away inside. Found fragment of wood inside with reverse scribing "W" and "S" still legible.
Oak, dead and down, S.50°W., 464.0 ft. Has not been opened. No scar visible, bark gone.
Set Brass cap alongside rock mkd:

County Surveyors Office
T 24 S R 6 W
S23|S24
S26|S25
1962

New BTs -6" W.Oak N.75½°W., 50.7 ft. mkd. S23 CS BT.
16" W.Oak N.58°E., 96.4 ft. mkd. T24S R6W S24 CSBT
7" W.Oak S.83°E., 167.2 ft. mkd. T24S R6W S25 CSBT
8" W.Oak S.32½°W., 317.1 ft. mkd. T24S R6W S26 CSBT
A fence corner, fences East, West and South, bears N.20°E., 10.0 ft. Cor. lies on S. slope of hill, near the top, top of hill nearly bare.

Fd. B.C., 1981, R. Ware, M 89-12
Fd. B.C., July 1992, M Heimbürger, M 112-50
Fd. Ok by Carl Sweeden, 5/2007 - 2007-0106

continued next page

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 7/23/2007 - C.S. File 67/24-3

Found - 2½" dia., brass cap properly mkd on 1¼" O.D. iron
pipe, firmly set, projects 10" above ground.
3"x5" sandstone with "+" chiseled on top is found on
south side of BC/IP. Stone projects 6" above
ground.
8" now 26" dia., W.Oak, fully healed double blaze,
bears S.32½°W., 317.1 ft. (agrees w/rec) 1962 BT
New - 33" dia., W.Oak double blazed & scribed "T24S R6W
S24 CS BT" bears N.32½°E., 97.5 ft.
18" dia., W.Oak double blazed & scribed "T24S R6W
S23 CS BT" bears N.21°W., 165.4 ft.
11" dia., Ash double blazed & scribed "T24S R6W
S26 CS BT" bears S.63°W., 356.2 ft.
Note - Corner lies at 3 way fence jct. with fences
extending east-west and south.
Compass decl. 16¼°E.