

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3137)

Set post cor. to secs. 13, 14, 23 and 24, from which
A W.Oak 13" dia., bears N.82°W., 64 lks. dist.
A W.Oak 17" dia., bears S.45°W., 93 lks. dist.
A W.Oak 14" dia., bears S.12½°E., 118 lks. dist.
A W.Oak 24" dia., bears N.41°E., 100 lks. dist.

F.C. Frear, Douglas Co. Surveyor - Wit: H.L. Eppstein, H.F. Crocker - Oct. 2, 1919 - C.S. File 1/1 and Field Book 47 Pages 1-13

I set a 6" x 12" x 24" sandstone rock as per old BTs all standing except the one in sec. 14.
I remark old BTs and also 3 new trees as follows:
10" Fir bears West, 1.11 ch. CS BT.
10" Fir bears North, 0.84 chs. CS BT.
6" Fir bears S.19½°E., 0.38 chs. CS BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; S.A. Bilow - August 1958 - C.S. File 49/83-19

Found - Rock at cor. as recorded by Frear and find Frear's BTs thus:
10" now 30" Fir, West 73.3 ft., shows faint scar, I do not open.
10" now 24" Fir stump shows scar, I do not open, North, 55.4 ft.
6" now 14" Fir S.19½°E., 25.1 ft. North side of tree badly burned, no scribing found.
Orig. 14" now 36" W.Oak S.12½°E., 77.9 ft., partly opened, face shows good scribing "T"
Orig. 17" now 34" dead W.Oak S.45°W., 61.4 ft., shows good scar, I do not open.
Orig. NW BT gone - Orig. NE BT, now down.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 6 W
S14|S13
S23|S24
1958

New BTs -14" R.Fir bears South, 13.0 ft. scribed S23 T24S R6W CS BT.
6" R.Fir bears N.74°E., 16.2 ft. scribed S13 CS BT.
26" B.Oak bears S.23°E., 44.7 ft. scribed S24 T24S R6W CS BT.

(Cont. Next Page)

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

30" R.Fir bears N.88°W., 73.3 ft. scribed S14 T24S R6W CS BT.
Fd. and used corner in BLM resurvey by Berry & Akin, Cadastral Surveyors and Baughman, R.L.S. #536, under Contracts #826 and 856 (DCSO records, Vol. 37 Pages 15234-35)