

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder and Henry Gile, Deputy Surveyors,  
under Contract #31 dated April 7, 1853 (DCSO records Vol. 8  
Page(s) 3138)

-----  
Set ¼ sec. post, from which

A Y.Oak 15" dia., bears N.79°W., 67 lks. dist.

A Y.Oak 13" dia., bears N.62°E., 62 lks. dist.

Not Fd. by DCSO VRT, 8/18/1970 (added 3/28/2017) C.S. File  
52/102-13: A N-S fence runs along sec. line and has been  
cleared for pasture in Sec 14. Logged & cleared in Sec. 13 -  
No OBTs fd.

BLM resurvey by Daniel Berry and Charles Akin, Cadastral  
Surveyors, and Glenn Baughman, LS #536 under Group #'s 826  
and 856, Surveyed Sept. 1973/Aug. 1975 (DCSO records Vol. 37  
Page(s) 15235)

-----  
Point for the ¼ sec. cor. of secs. 13 and 13, at  
proportionate distance; there is no remaining evidence of the  
original corner.

Set an iron post, 28" long, 2½" dia., 22" in the ground with  
brass cap mkd:

T 24 S R 6 W

1/4

S 14 | S 13

1973

from which

A Fir 16" dia., bears East, 18 lks. dist., mkd. ¼ S13 BT.

A Madrone 5" dia., bears N.64½°W., 24 lks. mkd. ¼ S14 BT.