

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3138)

Set post cor. to secs. 11, 12, 13 and 14, from which
A Y.Oak 13" dia., bears N.52½°W., 120 lks. dist.
A Y.Oak 16" dia., bears N.73°E., 72 lks. dist.
A Y.oak 12" dia., bears S.38°W., 25 lks. dist.
A Y.Oak 17" dia., bears S.79°E., 48 lks. dist.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, V. Perron, crew - Aug. 13, 1970 - C.S. File 52/102-8

Found - Orig. 16" now 24" W.Oak, alive, N.73°E., 47.5 ft., shows faint scar.
Orig. 12" now 20" W.Oak, alive, S.38°W., 16.5 ft. open and find reverse scribe.
Orig. 17" now 25" W.Oak, alive, S.79°E., 31.7 ft. previously opened, nearly rehealed. Rescribed "S13" above old scar.
NW orig. BT, down and badly decayed.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 6 W
S 11 | S 12
S 14 | S 13
1970

New BTs -13" W.Oak S.8°E., 25.0 ft. mkd. T24S R6W S13 CS BT.
12" D.Fir N.66°E., 22.8 ft. mkd. T24S R6W S12 CS BT
9" W.Oak N.20°W., 29.1 ft. mkd. T24S R6W S11 CS BT.
50" D.Fir S.56°W., 12.3 ft. bark scribed T24S R6W S14 CS BT.

Corner lies on West slope in Oak, Laurel and scattered Fir.

Cor. Fd. and used in BLM resurvey by Berry and Akin and Glenn Baughman, under Contract #'s 826 and 856, surveyed Sept. 1973/Aug. 1975 (DCSO records, Vol. 37 Page 15236)

~~Fd. OK, July 1994, M-120-42~~ This survey has no information for this corner, added in error. DCSO JC 11/16/2023

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew - For: US Department of Interior, BLM - Mean Mustard & Galagher Canyon 1- Task A - Aug. 2023 - M185-5 A-D

Found - 2½" County Surveyors Brass Cap (properly mkd), 1.4' above ground from which:
A 23" Oak bears S.38°W., 16.5' with partially healed blaze (1853) Continued next page

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 55" Fir snag bears S.50°W., 12.1' with illegible bark scribe (1970)
A 12" Oak bears N.20°W., 29.5' with healed blaze and sign (1970)
A 25" Fir bears N.66°E., 23.1' with healed blaze and sign (1970)
A 16" Oak bears S.8°E., 25.2' with healed blaze and sign (1970)
A Roothole bears N.73°E., 49.3' with oak trunk alongside (1853)
(Set chaining nail at side center, BT signs on front and rear, and painted red band for existing BTs)