

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3139)

Set ¼ sec. post, from which
 An Ash 8" dia., bears N.67½°W., 24 lks. dist.
 An Ash 8" dia., bears S.83½°E., 56 lks. dist.

Not searched for - by DCSO VRT, 8/18/1970 (added 3/28/2017)
C.S. File 52/102-13: Small Ash trees used for BTs, we do not search.

Survey by Don E. Garrett - For: Bill Rees - Sept. 1973 -
M 49-38

Set Brass cap mkd: ¼ S11, S12 T24S R6W RPLS 544 1973.
 13" Fir bears N.41°30'E., 62.3 ft. scribed ¼ S12 BT.
 8" Fir bears N.74°W., 79.3 ft. scribed ¼ S11 BT.

Cor. Fd. and used in BLM resurvey by Berry, Akin and Baughman, surveyed 1973/1975 (DCSO records, Vol. 37 Page 15238)

Fd. OK, Aug. 1992, R. Dolan, M 115-49