

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3139)

-----  
Set post cor. to secs. 1, 2, 11 and 12, from which  
A W.oak 18" dia., bears N.86°E., 80 lks. dist.  
A Y.Oak 11" dia., bears S.31 3/4°E., 133 lks. dist.  
A W.Oak 20" dia., bears S.76°W., 227 lks. dist.  
A W.oak 8" dia., bears N.45½°W., 239 lks. dist.

-----  
GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3173)

-----  
The cor. of secs. 1, 2, 11 and 12, Post gone, small stake setting at corner. I set a Fir post 4 ft. long, 4" sq., 24" in the ground mkd. T24S S1 on NE.; R6W S12 on SE.; S11 on SW.; and S2 on NW. faces, with 5 notches on the South and 1 notch on the East edges, from which  
A W.Oak 18" dia., bears N.86°E., 80 lks. dist. mkd. T24S R6W S1 BT.  
A Y.Oak 11" dia., bears S.31 3/4°E., 133 lks. dist., mkd. T24S R6W S12 BT.  
A W.Oak 20" dia., bears S.76°W., 22 lks. dist. mkd. T24S R6W S11 BT.  
A W.Oak 8" dia., bears N.45½°W., 239 lks. dist., mkd. T24S R6W S2 BT.

-----  
Survey by Don E. Garrett - For: Bill Rees - Sept. 1973 - M 49-38

-----  
Set by proportionate measurement.  
Set Brass cap mkd: S1, S2, S11, S12, T24S R6W RPLS 544 1973  
8" W.Oak bears S.82°E., 26.1 ft. scribed S12 T24S R6W BT.  
7" W.Oak bears N.32°E., 25.1 ft. scribed S1 T24S R6W BT.  
6" W.Oak bears N.34°W., 22.7 ft. scribed S2 T24S R6W BT.  
6" W.Oak bears S.21°W., 19.8 ft. scribed S11 T24S R6W BT.

-----  
BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, and Glenn Baughman, LS #536 under Group #'s 826 and 856, Surveyed Sept. 1973/Aug. 1975 (DCSO records Vol. 37 Page(s) 15238-39)

-----  
The Sec. cor., determined at record bearing and distance from which the remains of the original bearing trees:  
A W.Oak 26" dia., bears N.86°E., 80 lks. dist., with fragm. scribe marks visible in negative on overgrowth.  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

A decayed Oak stump, size indeterminate, bears S.76°W.,  
 227 lks. dist., no marks visible.

At the corner point

Set an iron post, 28", long, 2½" dia., 24" in the ground,  
 with brass cap mkd:

T 24	S R 6 W
S 2	S 1
S 11	S 12
1973	

from which new bearing trees

- A Fir 7" dia., bears N.49°E., 44½ lks. dist., mkd. T24S R6W S1 BT.
- A Fir 7" dia., bears S.86°E., 47 lks. dist., mkd. T24S R6W S12 BT.
- A Fir 6" dia., bears S.27°W., 35 lks. dist, mkd. T24S R6W S2 BT.
- A W.Oak 7" dia., bears N.10°W., 20 lks. dist., mkd. T24S R6W S2 BT.

From this point, a local corner established and recorded by  
 Garret in 1973, bears S.13¼°W., 0.056 chs. dist., monumented  
 with an iron post, 2½" dia., firmly set, projecting 8" above  
 ground, with brass cap mkd. T24S R6W S1 S2 S11 S12 RPLS 544  
 1973, from which bearing trees mkd. by Garrett:

- A W.Oak 7" dia., bears N.32°E., 38 lks. mkd. S1 T24S R6W  
 on double blaze.
- A W.Oak 8" dia., bears S.82°E., 39½ lks. dist., mkd. S12  
 T24S R6W on double blaze.
- A W.Oak 6" dia., bears S.21°W., 30 lks. dist., mkd. S11  
 T24S R6W on double blaze.
- A W.Oak 6" dia., bears N.34°W., 34½ lks. dist., mkd. S2  
 T24S R6W on double blaze.

Douglas Co. Surveyors Office - L.E. Monrean, P.L. Earle, crew  
 - March 25, 1975 - C.S. File 57/21-1

- 
- Found - 1973 Brass cap set by D. Garrett, from which
- A W.Oak 7", bears N.32°E., 25.2 ft. scribed S1 T24S R6W.
  - A W.Oak 8", bears S.82°E., 26.1 ft. scribed S12 T24S R6W.
  - A W.Oak 6", bears S.21°W., 19.9 ft. scribed S11 T24S R6W.
  - A W.Oak 6", bears N.34°W., 22.8 ft. scribed S2 T24S R6W.
- Found - 1973 BLM brass cap, from which
- A Fir 7", bears N.47°E., 29.4 ft. (Rec. N.49°E.)  
 scribed T24S R6W S1 BT.

