

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3140)

Set ¼ sec. post, from which
A Laurel 15" dia., bears N.72½°E., 15 lks. dist.
A Fir 18" dia., bears N.34°W., 48 lks. dist.

Survey by Wilford N. Haines - For: E.G. Whipple and Harold Woolley - Sept. 1957 - M 5-52

Found - 18" Fir N.34°W., 48 lks. (snag)
Set 1" x 1" x 36" I.Rod with brass cap inscribed "Wilford N. Haines Drain, Oregon #239 Survey Pt."
Scribed -40" Fir N.52°W., 41.8 ft.
10" Fir S.65°40'E., 53.0 ft.

Mark Smalley - For: Roseburg Forest Products - May 30, 1997 - C.S. 65/13-9F

Mon. Fd.- 1"x 1" iron T post with 1" brass cap inscribed "Wilford N. Haines Drain, Oregon #239 Survey Pt".
Bt's Fd.- 18" Fir snag, (10' tall), N.34°W., 48 lks. scribe visible, OBT.
40" Fir, N.52°W., 41.8' down
10" Fir, S.65°40'E., 53' stump (6" high)
New Bt's- 6" Oak, N.42°W., 6.8' "¼ S Bt"
7" Fir, S.87°E., 22.4' "¼ S Bt"
7" Fir, N.8°E., 14.3' "¼ S Bt"
8" Oak, S.73°E., 3.7' "¼ S Bt"

Found OK by D. Edwards, May 2002 - M140-13