

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3138)

Set $\frac{1}{4}$ sec. post, from which
A W.Oak 18" dia., bears S.47 $\frac{1}{2}$ °W., 117 lks. dist.
A Y.Oak 20" dia., bears N.28°W., 77 lks. dist.

F.C. Frear, Douglas Co. Surveyor - Wit: H.L. Eppstein and H.F. Crocker - Oct. 2, 1919 - C.S. File 1/1 and Field Book 47 Pages 1-13

Re-established as per old BTs, both standing but badly decayed. I set a 4" x 4" x 36" Oak stake, from which
A 5" W.Oak bears N.55 $\frac{3}{4}$ °E., 0.17 chs. CS BT.
A 36" B.Oak bears S.17°W., 0.105 chs. CS BT.

BLM resurvey by Daniel Berry and Charles Akin, Cadastral Surveyors and Glenn Baughman, RLS #536, under Group #'s 826 and 856, Surveyed Sept. 1973/Aug. 1975 (DCSO records Vol. 37 Page(s) 15234)

Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 $\frac{1}{2}$ " dia., 22" in the ground, with brass cap mkd: T 24 S R 6 W

$\frac{1}{4}$ $\frac{S 13}{S 24}$
1973

from which

A W.Oak 10" dia., bears N.43 $\frac{1}{2}$ °E., 17 lks. dist., mkd. $\frac{1}{4}$ S13 BT.

A W.Oak 12" dia., bears S.69 $\frac{1}{2}$ °E., 34 lks. dist., mkd. $\frac{1}{4}$ S24 BT.