

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors,
under Contract #31 dated April 7, 1853 (DCSO records Vol. 8
Page(s) 3139)

Set $\frac{1}{4}$ sec. post, from which
A Y.Oak 8" dia., bears N.20°E., 81 lks. dist.
A Y.Oak 8" dia., bears S.62 $\frac{1}{2}$ °W., 31 lks. dist.

BLM resurvey by Daniel Berry and Charles Akin, Cadastral
Surveyors and Glenn Baughman, LS #536, under contract #'s 826
and 856, surveyed Sept. 1973/Aug. 1975 (DCSO records Vol. 37
Page(s) 15237)

Point for the $\frac{1}{4}$ sec. cor., at proportionate distance; there
is no remaining evidence of the original corner.
Set an iron post 28" long, 2 $\frac{1}{2}$ " dia., 22" in the ground, with
brass cap mkd. T 24 S R 6 W

$\frac{1}{4}$ $\frac{S\ 12}{S\ 13}$
1973

from which
A Fir 15" dia., bears N.48 $\frac{1}{2}$ °E., 67 lks. dist., mkd. $\frac{1}{4}$ S12
BT.
A Fir 15" dia., bears S.34 $\frac{1}{2}$ °W., 13 lks. dist., mkd. $\frac{1}{4}$ S13
BT.