

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; and 31 of T24-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original -Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 7 Page(s) 3084)

Set ¼ sec. post, from which
A Y.Oak 14" dia., bears N.30½°W., 28 lks.
A Y.Oak 26" dia., bears N.46¼°E., 83 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey and Clete Putnam - March 17, 1960 - C.S. File 49/124-36

Found - Orig. 14" now down and partly rotted Oak. Shows good reverse scribing on chip of old face "BT"
Orig. NE BT, now down, face down.

Set brass cap at corner mkd: County Surveyors Office
¼ S36 | S31 T24S
R6W R5W
1960

New BTs -12" W.Oak bears N.57°W., 6.5 ft. scribed ¼ S36 CSBT
11" W.Oak bears S.83°E., 12.9 ft. scribed ¼ S31 CSBT

Douglas County Surveyors Office - Randall Smith & Stephen Flause - May 22, 1997 - C.S. 64/75-2

Mon. Fd- 2½" dia. Brass cap on a 1½" O.D. iron pipe protrudes 12" above ground. 1960

Accessories Fd.-
OBT's now gone
12" now 22" dia. W.Oak, with fully healed blaze, bears N.57°W., 6.5' (agrees with rec.) 1960
1960 SE Bt now gone

New Accessories -
16" dia. W.Oak, double blazed and scribed "¼ S31 CS BT", bears N.47°E., 38.5'.
21" dia. W.Oak, double blazed and scribed "¼ S31 CS BT", bears S.88°E., 52.6'.
28" dia. B.Oak, double blazed and scribed "¼ S36 CS BT", bears S.73½°W., 168.9'.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 9/13/2007 - C.S. File 67/24-20

Fd. as per 1997 rec.