

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T24-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original -Robert Elder, under Contract #31 dated April 7, 1853 (DCSO records Vol. 7 Page(s) 3082)

-----  
Set post cor. to secs. 7, 12, 13 and 18, from which  
A Y.Oak 20" dia., bears S.32°E., 14 lks.  
A Y.Oak 20" dia., bears N.57½°E., 26 lks.  
A Y.Oak 14" dia., bears N.41°W., 50 lks.  
A Y.Oak 9" dia., bears S.79½°W., 62 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey and Clete Putnam - Feb. 1960 - C.S. 49/124-17

-----  
Found - Orig. 14" now 30" B.Oak, N.41°W., 33.0 ft., previously opened and rescribed years ago, not on old face. I find parts of good scribing on old face.

Find remains of old Oaks that check for original NE. and SW. BTs.

Set Brass cap at corner mkd: County Surveyors Office

S 12 | S 7 T24S  
R6W S 13 | S18 R5W  
1960

New BTs -10" R.Fir bears S.72°E., 51.4 ft. scribed S18 T24S  
R5W CS BT.  
16" R.Fir bears N.68°E., 46.4 ft. scribed S7 T24S  
R5W CS BT.  
10" R.Fir bears N.30°W., 19.3 ft. scribed S12 T24S  
R6W CS BT.  
8" R.Fir bears S.51°W., 3.5 ft. scribed S13 CS BT.

Cor. Fd. and used in BLM resurvey by Berry and Akin, Cadastral Surveyors; and Baughman, under Contract #52500-CT5-1116, Group #'s 826 and 856 - surveyed Sept. 1973/Aug. 1975 - (DCSO records, Vol. 37 Page 15233)