

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T24-5

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - James E. Freeman Deputy Surveyor, under Contract #1, dated May, 28, 1851 (DCSO records Vol. 7 Page(s) 3081)

Set post cor. to secs. 6, 7, 1 and 12, from which
A Y.Oak 12" dia., bears S.25°E., 34 lks.
A Y.Oak 9" dia., bears S.24°W., 52 lks.
A Y.Oak 26" dia., bears N.70°W., 38 lks.
A W.Oak 10" dia., bears N.80°E., 78 lks.

Survey by Gerald D. Riley - For: Webb and DeBaun - May 1970
-C.S. File 55/150

Set Brass cap marked RS 705, and scribe
8" Fir N.51°E., 12.5 ft. "S6 RS 705 BT"
14" Fir S.77°E., 26.6 ft. "S7 RS 705 BT"
6" Fir S.40°W., 15.0 ft. "S12 RS 705 BT"
8" Fir N.39°E., 26.9 ft. "S1 RS 705 BT"

Fd. OK, July 1994, D. Bentz, M 120-42

DCSO-GIS Corner visitation - 5/30/2007 - Typed: 1/21/2011 -
C.S. File 67/33-1

Monument - 2½" BC/SSP

David Edwards - For: Art Jones - Oct. 2011 - M163-3

Found - Brass cap per C.S. 55/150 (Riley)
All BTs by Riley are now stumps.
New BTs- A 7" dia., Fir bears N.66°E., 21.7 ft. scribed "T24S
R5W S6 BT"
An 8" dia., fir bears S.41°W., 26.5 ft scribed "T24S
R6W S12 BT"
No other trees nearby.
A 6 ft. steel fence post is set 1 ft. ± South.