

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Tsp. Cor. (NE cor. Sec. 1)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original -Robert Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2342-43)

Set post, cor. to Tps., 23 and 24 S., bet. Rs., 5 and 6 W., from which

- A Y.Oak 18" dia., bears N.2°W., 34 lks.
- A Y.Oak 14" dia., bears N.17°E., 55 lks.
- A Y.Oak 18" dia., bears S.49°E., 78 lks.
- A Y.Oak 15" dia., bears S.43°W., 77 lks.

Oscar Thiel - 1901/1909(?) - C.S. File 64/48 Page 17

NE Township Corner
Set - A fir post for Township corner
Mkd - Black Oak N.19°W., 62 lks.

BLM resurvey by Otis Gould, Joseph Gawron, Orville Eggen, Cadastral Surveyors, under Group #244, surveyed, June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12634-35)

The cor. of Tps. 23 and 24 S., Rs. 5 and 6 W., is determined at the cor. of fences, extending N., S., E., and W., which point has been recognized and accepted by local residents for more than 40 years.

At the corner point

Set an iron post, 3 ft. long, 3" dia., 27" in the ground, with brass cap mkd:

T23S	
R6W	R5W
<u>S36</u>	<u>S31</u>
S 1	S 6
T24S	
1943	

from which

- A Fir 60" dia., bears N.57½°E., 60 lks. dist., mkd. T23S R5W S31 BT.
- A Fir 35" dia., bears S.62½°E., 127 lks. dist., mkd. T24S R5W S6 BT.
- A Fir 36" dia., bears S.18½°W., 177 lks. dist., mkd. T24S R6W S1 BT.
- A Fir 38" dia., bears N.83½°W., 280 lks. dist., mkd. T23S R6W S36 BT.

Cor. Fd., April 1956, G. Gardner, M 2-61

(Cont. Next Page)

TOWNSHIP 24 RANGE 06 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Tsp. Cor. (NE Cor. Sec. 1)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - L.E. Monrean and A.V. Cangie,
crew - April 22, 1974 - C.S. File 57/21-10

Found - USGLO brass cap properly mkd. and dated 1943.
50" Fir stump with good scar bears N.58°E., 43.0 ft.
(Rec. N.57½°E., 39.6 ft.)
38" Fir stump, blazed, scribe rotted, bears S.59°E.,
83.8 ft. (Rec. S.62½°E., 83.8 ft.)
36" Fir stump, blazed, some scribing visible. Blazed
area mainly rotted. Bears S.18°W., 119.8 ft.
(Rec. S.18½°W., 116.8 ft.)
48" Fir, blown down and blazed, bears N.84½°W., (?)
ft. (Rec. N.83½°W., 184.8 ft.) (Distance
indeterminate)
New BTs -9" Fir bears N.66°W., 30.3 ft. scribed T23S R6W S36
CS BT.
30" Fir bears N.85°E., 30.7 ft. scribed T23S R5W S31
CS BT.
16" Fir bears S.7½°E., 66.2 ft. scribed T24S R5W S6
CS BT. (Dist. 67.90 @-13°=)
10" Fir bears S.57°W., 27.1 ft. scribed T24S R6W S1
CS BT.

Corner lies in wooded area, Madrone and Fir, and is located
at intersection of fences running southerly, easterly and
westerly.

Fd. OK, July 1993, M 117-52

Found OK by D. Edwards, May 2002 - M140-13

DCSO-GIS Corner visitation - 5/25/2004 - Typed: 1/20/2011 -
C.S. File 67/33-1

Monument - 3.25" BC/IP Comment - OK