

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T24-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3195)

-----  
Set post cor. secs. 19, 30, 24 and 25, from which  
A Fir 9" dia., bears N.28°W., 36 lks. dist.  
A Fir 6" dia., bears S.75°W., 20 lks. dist.  
A Fir 36" dia., bears N.4°E., 13 lks. dist.  
A Cedar 12" dia., bears S.70°E., 25 lks. dist.

Fd. Hathorn's BTs and used in GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3272 and 3278)

-----  
(On page 3272)  
Trees were described as above)  
(On page 3278)  
"I can only account for the difference in description of bearing trees in this way. I only ran to this cor. to verify my work and did not take description of BTs. I got Mr. D.W. Applegate to copy the notes for Surveyor Generals office and in the absence of other notes, I think he must have taken description from notes furnished by Surveyor General and the error was overlooked by myself."

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3219-20)

-----  
At sec. cor., which is a post, so badly decayed that the marks are almost entirely obliterated, from which  
A Cedar 12" dia., bears S.70°E., 25 lks. dist.  
The other bearing trees described in notes furnished me are all destroyed.  
I set a new post, 4 ft. long, 4" sq., 24" in the ground for cor., marked T24S S19 on NE.; R8W S30 on SE.; R7W S25 on SW.; and S24 on NW. faces, with 2 notches on S. and 4 notches on N. edges, from which  
The above Cedar bears S.70°E., 25 lks. dist. mkd. T24S R8W S30 BT.  
and mark new trees as follows:  
A Maple 10" dia., bears N.17°E., 75 lks. dist. mkd. T24S R7W S19 BT.  
A Maple 8" dia., bears S.88°W., 57 lks. dist. mkd. T24S R8W S25 BT.  
A Fir 60" dia. N.51°W., 79 lks. dist. mkd. T24S R8W S24 BT

(Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T24-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - June 30, 1958 - C.S. File 49/41-17

-----  
Found three BTs as recorded by Chandler in 1893:  
10" Maple now 24", N.17°E., 49.5 ft. We make dist. 44.0 ft. Open face, good scribing "4 /".  
8" now 12" Maple stub, I open and find good scribing "BT", S.88°W., 37.6 ft.  
60" Fir stump, I open near base and find good scribing "BT", N.51°W., 52.1 ft. We make dist. 46.6 ft.  
Stump hole that would check bearing. We make dist. 13.5 ft., rec. 16.5 ft. for orig. 12" Cedar S.70°E., 16.5 ft  
Set Brass cap at cor. mkd: County Surveyors Office

	T	24	S		
R8W	S	24	S	19	R7W
	S	25	S	30	
				1958	

New BTs and bearing object:  
10" Cedar bears S.10½°W., 38.6 ft. scribed S25 T24S R8W CS BT.  
I chisel 4" + and B.O. 5 ft. above ground on 10 ft. high sandstone bluff which faces West, S.45°E., 7.8 ft.  
24" Maple bears N.17°E., 44.0 ft. scribed S19 T24S R7W CS BT.  
14" W.Fir bears N.82°W., 64.3 ft. scribed S24 T24S R8W CS BT.

Fd. OK, DCSO Sept. 21, 1971 - C.S. File 54/55-30  
Fd. OK Nov. 20, 1981 by Les Roberts - M 90-12  
Found OK by R. Rice, June 2003 - M142-47

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2102, surveyed May 2005 - Jan. 2006 - (DCSO records Vol. 56 Page(s) 22311 & Plat T24-8 2011)

-----  
The cor. of secs. 19, 24, 25, & 30, on the E. bdy of the Tp., remonumented by the DCSO in 1958, monumented with an iron post 1¼" dia., firmly set, projecting 18" above ground, with brass cap (properly) mkd.  
from which the remains of BTs mkd by Chandler in 1894  
A maple, 33" dia., bears N.14¾°E., 45.8 ft. with fragmentary scribe marks visible on a partially healed blaze. (Rec. N.17°E., 49.5 ft. rescribed by the DCSO in 1958)  
A maple 22" dia., bears S.84¾°W., 37.6 ft. with no marks visible (Rec. S.88°W.)

continued next page

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T24-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed fir stump, size indeterminate bears N.51°W., 45.3 ft. with fragmentary scribe marks visible on blaze face lying alongside (Rec. 52.1 ft)

and accessories mkd by the DCSO

A chisel mark "+" on a vertical rock face, 5 ft. above ground, bears S.48°E., 7.9 ft. with chisel marks B0 alongside.

A cedar, 15" dia., bears S.9¼°W., 38.5 ft. with a healed double blaze.

A fir, 27" dia., bears N.83¾°W., 61.3 ft. with a healed double blaze.

The geographic position (NAD 1983(CORS)) of corner of secs 19, 24, 25, & 30, on the east boundary of the township was determined by a tie from a temporary GPS control point, established utilizing a dual frequency, carrier phase GPS receivers.

Latitude 43°27'42.68"N

Longitude 123°35'06.84"W

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22389-90)

-----  
The cor. of secs 19, 24, 25, and 30, on the E. bdy. of the Tp., remonumented by the Douglas County Surveyors Office in 1958, monumented with an iron post, 1¼" dia., firmly set, projecting 18" above ground, with brass cap (properly) mkd. from which the remains of bearing trees mkd. by Chandler

A maple, 33" dia., bears N.14¾°E., 45.8 ft., with scribe marks BT visible on a partially healed blaze. (Record, N.17°E., 49.5 ft. Rescribed by the Douglas County Surveyors Office in 1958.)

A maple, 22" dia., bears S.84¾°W., 37.6 ft., with no marks visible. (Record, S.88°W.)

A decayed fir stump, size indeterminate, bears N.51°W., 45.3 ft., with fragmentary scribe marks visible on blaze face lying alongside. (Record, 52.1 ft.)

and accessories mkd. by the Douglas County Surveyors Office

A chisel mark "+" on a vertical rock face, 5 ft. above ground, bears S.48°E., 7.9 ft., with chisel marks B0 alongside.

A cedar, 15" dia., bears S.9¼°W., 38.5 ft., with a healed double blaze.

A fir, 27" dia., bears N.83¾°W., 61.3 ft., with a healed double blaze.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T24-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 4/16/2019 (Filed 11/18/2021) - C.S. File 67/50-25

-----  
Found - 1958 DCS0 2½" dia., brass cap on a 1" I.D. iron pipe  
Cap properly marked as described, projecting 16" above ground.

A 37" dia., Maple with a previously opened blaze, now rotted out with no marks; bears N.14¾°E., 45.8 ft. OBT (per 2005/2006 BLM rec.)

A 27" dia., Maple with no blaze scars (trunk is sprout from root crown of 1893 NW BT) The root crown bears S.88°W., 37.6 ft. (as per 1893 rec)

A 37" dia., Maple with a previously opened now rotted out blaze; bears N.14¾°E., 45.8 ft. 1958 (per 2005 BLM record) (Noted as New BT & 1893 BT)

A 4" (cross piece length) "+" carved in vertical sandstone bluff; bears S.48°E., 7.9 ft. 1958 (per 2005 BLM rec.)

A 16" dia., I.Cedar with a fully healed double blaze; bears S.9¾°W., 38.5 ft 1958 (per 2005 BLM)

A 28" dia., W.Fir tipped out and fallen on face. Root hole of this tree bears N.83¾°W., 61.3 ft. 1958 (per 2005 BLM rec)

New - 4" MAG NAIL driven in top center of a solid 24" dia., 1½ ft tall D.Fir stump; bars N.48°W., 85.6.

A rough stone collar is built around found BC/IP. Monument now projects 6" above stone collar.

Note - BC monument is at foot of southerly wall of hole like draw and is approx 100 ft. SE frm main forest access road.