

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only, T24-8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3220-21)

-----  
Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 18, 19, 13 and 24, marked T24S S18 on NE.; R7W S19 on SE.; R8W S24 on SW.; and S13 on NW. faces, with 3 notches on S. and N. edges, from which  
A Fir 30" dia., bears N.21°E., 213 lks. dist. mkd. T24S R7W S18 BT.  
A Fir 24" dia., bears S.80°E., 180 lks. dist. mkd. T24S R7W S19 BT.  
A Fir 14" dia., bears S.76°W., 65 lks. dist. mkd. T24S R8W S24 BT.  
A Fir 14" dia., bears N.58°W., 136 lks. dist. mkd. T24S R8W S13 BT.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3261 and 3278 and 3230)

-----  
(Page 3261)  
(Found corner and BTs as described above.)  
  
(Page 3278)  
I obliterate marks on cors. established by Deputy Chandler referring to secs. for which closing cors. stand. June 18, 1896.  
  
(Page 3230)  
Fd. and used same cor. for resurvey of E. bdy. Sec. 13, T24-8

Survey by Les Roberts - For: International Paper Co. - Nov. 20, 1981 - M 90-12

-----  
Found - 22" downed Fir bears S.76°W., 42.9 ft. with scribe visible.  
30" Fir stub bears N.21°E., 141.1 ft., no marks.  
38" Fir stub bears N.59°W., 89.8 ft., no marks.  
40" Fir bears S.79°E., 123.0 ft., no marks.  
(Distances to BTs measured on slope.)  
Set 1½" x 36" I.P. and brass cap.  
New BTs- 13" Fir bears N.52°W., 24.8 ft., scribed.  
24" Fir bears S.18°W., 24.2 ft., scribed.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only, T24-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Ronald Rice, Ward NW INC. - Roseburg Resources Co. - 6/2003 - M142-47

- 
- Found - 2½" brass cap dated 1981 w/the following accessories  
20" Fir bears N.52°W., 24.8' (healed face)  
32" Fir bears S.18°W., 24.2' (healed face)
- New BT - 31" D.Fir bears N.74°E., 20.2' blazed, scribed "X BT" at base.
- Note - Existing corners or corner established as a result of this survey have a galvanized steel post adjacent to the corner monument and accessories have red painted bands & BT tags where appropriate.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22392)

-----

The cor. of secs. 13 and 24 only, on the E. Bdy. of the Tp., remonumented by Roberts, in 1981, and perpetuated by Rice, in 2003, monumented with an iron post, 1¾" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd. from which the remains of the orig. bearing trees

A fir, 52" dia., bears S.80°E., 118.8 ft., with no marks visible on an opened blaze.

A fallen, decayed fir, size indeterminate, bears S.72½°W., 42.9 ft., with fragmentary scribe marks visible on an opened blaze. (Record, S.76°W.)

A decayed fir stump, size indeterminate, bears N.59¾°W., 84.8 ft., with no marks visible. (Record, N.58°W., 89.7 ft.)

and bearing trees mkd. by Roberts

A fir, 33" dia., bears S.16¼°W., 23.7 ft., with a healed blaze.

A fir, 21" dia., bears N.51¾°W., 25.0 ft., with a healed blaze.

and a bearing tree mkd. by Rice

A fir, 23" dia., bears N.72¾°E., 20.3 ft., with a healed blaze.