

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION W 1/4 Cor. Sec. 18 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22394)

-----  
Point for the ¼ sec. cor. of sec. 18 only, on the E. bdy. of the Tp., at proportionate distance. There is no remaining evidence of the orig. cor.

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, with brass cap mkd.

T 24 S  
R8W | R7W  
      | ¼  
      | S18  
      2005

from which

A fir, 14" dia., bears N.20°E., 25.1 ft., mkd. ¼ S18 BT.

A fir, 10" dia., bears S.43¼°E., 12.0 ft. mkd. X BT.

Deposit a magnet in a white plastic case, at the base of the stainless steel post.