

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION CC for Secs. 7 & 18 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3263)

At point of intersection, I set a post 4 ft. long, 4" sq., 24" in the ground for closing cor. to secs. 7 and 18, mkd. CC T24S R7W on E.; S7 on N.; and S18 on S.; with 4 notches on S. and 2 notches on N. faces, from which

A Fir 24" dia., bears N.82°E., 35 lks. dist. mkd. T24S R7W S7 BT.

An Alder 15" dia., bears S.72½°E., 56 lks. dist. mkd. T24S R7W S18 BT.

A Fir 10" dia., bears S.17½°W., 56 lks. dist. mkd. T24S R7W CC S7 and 18 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - July 15, 1960 - C.S. 49/41-30

Found - Fir stump now 60", (Orig. 40" instead of 10"), has been opened and scribe visible, "24S 7W S7 & 18 CC", measured N.17½°E., 37 ft., slope dist. for corner.

Fir tree, now 40", N.82°E., 23.1 ft., shows good scars.

No trace of SE. BT found.

Corner lies about 15 ft. South of small creek.

At corner, Set Brass cap at cor. mkd: County Surveyors Office

T24S R8W CC | S 7 R7W
 | S 18

1960

Blaze and scribe new tree:

14" Red Cedar S.67°E., 31.4 ft. mkd. T24S R7W CC S18 CS BT.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22395-6)

The true point for the closing cor. of secs. 7 and 18, on the E Bdy of the Tp., at the intersection with the section line. Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, with brass cap mkd.

T 24 S
R8W | R7W
S12 | c S7
 | c S18
2005

continued next page

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 18 only, (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which
A fir, 14" dia., bears S.40¼°E., 16.5 ft., mkd. X BT.
Deposit a magnet in a white plastic case, at the base of the stainless steel post.
From this point, the orig. closing cor. of secs. 7 and 18, established by Whipple in 1893-94, remonumented by the Douglas County Surveyors Office in 1960, bears N.89°58'28"W., 8.55 ft., monumented with an iron post, 1¼" dia., firmly set, projecting 13" above ground, with brass cap (properly) mkd. from which the remains of the orig. bearing trees
A fir, 54" dia., bears N.82°E., 23.1 ft., with a healed blaze.
A sawed and decayed fir stump, 54" dia., bears S.14½°W., 33.3 ft., with scribe marks 7W 7 & 18 visible on a partially opened blaze. (Record, S.17½°W., 37.0 ft.) and a BT mkd. by the Douglas County Surveyors Office
A cedar, 28" dia., bears S.66¼°E., 31.7 ft., with a healed blaze.
Add the marks AM to the brass cap.