

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3222-23)

Set a post 3½ ft. long, 3" sq., 24" in the ground for ¼ sec. cor., marked ¼ S on W. face, from which
A Fir 30" dia., bears N.80°E., 28 lks. dist. mkd. ¼ S BT.
A Fir 24" dia., bears S.22°W., 18 lks. dist. mkd. ¼ S BT.

Fd. and used in GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3232)

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - For: Martin Box Co. - Dec. 21, 1959 - C.S. File 52/6-1

Found - Orig. 30" now 45" Fir stump N.80°E., 18.5 ft. I open and find good scribing "BT".
Orig. 24" now 52" Fir stump, shows good bark scribing "BT" S.22°W., 11.9 ft.
Set Brass cap at cor. mkd: County Surveyors Office
E ¼ S12 T24S R8W | R7W
1959
New BTs- 8" W.Fir bears S.60½°W., 32.1 ft. scribed ¼ S12 CSBT
8" Cedar bears N.69°W., 36.3 ft. scribed ¼ S12 CS BT

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22396-7)

The ¼ sec. cor. of sec. 12 only, on the E. Bdy. of the Tp., remonumented by the Douglas County Surveyors Office in 1959, monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd. from which the remains of the orig. bearing trees
A decayed fir stump, 43" dia., bears N.84½°E., 18.5 ft., with no marks visible. (Record, N.80°E.)
A decayed fir stump, 54" dia., bears S.28¾°W., 11.9 ft., with no marks visible. (Record, S.22°W.)
and bearing trees mkd. by the Douglas County Surveyors Office
A fir, 28" dia., bears S.59¾°W., 32.4 ft., with a healed blaze.
A cedar, 14" dia., bears N.70°W., 36.0 ft., with a healed blaze.