

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 100574

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T24-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 records Vol. 8 Page(s) 3223)

Set post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 1, 6, 7 and 12, marked T24S S6 on NE.; R7W S7 on SE.; R8W S12 on SW.; and S1 on NW. faces, with 5 notches on S. and 1 notch on N. edges, from which

- A Fir 18" dia., bears N.17°E., 64 lks. dist. mkd. T24S R7W S6 BT.
- A Fir 24" dia., bears S.8°E., 107 lks. dist. mkd. T24S R7W S7 BT.
- A Fir 20" dia., bears S.16°W., 59 lks. dist. mkd. T24S R8W S12 BT.
- A Fir 10" dia., bears N.39°W., 78 lks. dist. mkd. T24S R8W S1 BT.

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCS0 records Vol. 8 Page(s) 3232)

(Page 3232 and page 3266)
Found post and trees as described above)

(Page 3278)
I obliterate marks on cors. established by Deputy Chandler referring to secs. for which closing cors. stand. (June 18, 1896)

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - For: Martin Box Co. - Dec. 21, 1959 - C.S. File 52/6-2

Found - Orig. 20" now 20" D.Fir N.39°W., 51.5 ft. I open and find good scribing "S". This BT was 8" when scribed.

I find down Firs that check rec for SE. and SW. BTs.
No trace of orig. NE. BT.

Set brass cap at cor. mkd. County Surveyors Office 1959

T 24 S
R8W $\frac{S \ 1}{S \ 12}$ R7W

New BTs- Rescribe orig. 20" R.Fir N.39°W., 51.5 ft. "S1 T24S R8W CS BT"

10" R.Fir bears S.69°W., 12.7 ft. scribed "S12 T24S R8W CS BT."

(Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 100574

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T24-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Wit: Henrickson and Clark - Sept. 4, 1963 - C.S. File 51/163-10

Found - 10" D.Fir S.69°W., 12.7 ft., renewed BT, now stump.
20" D.Fir N.39°W., 51.5 ft., orig. BT, now 26" stump.
Scribed- 8" W.Fir S.5°W., 48.5 ft.
7" W.Fir N.61°W., 41.1 ft.
Corner falls in West lane of logging road, therefore, no iron pipe was set.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 1967 - C.S. File 54/55-8

Found - Orig. 20" D.Fir, now shattered snag, N.39°W., 51.5 ft., scribe visible.
No trace of other original BTs.
10" D.Fir now 6 ft. high stump, S.69°W., 12.7 ft. scribe visible.
8" now 10" W.Fir, alive, S.5°W., 48.5 ft., scribe visible.
7" now 12" W.Fir, alive, N.61°W., 41.1 ft., nearly healed blaze.

Set Brass cap at cor. mkd: County Surveyors Office, 1967

T 24 S
R8W R7W
S 1 |
S 12 |

Set 6 ft. steel fence post alongside brass cap.
Corner lies on left shoulder of old logging road, 5 ft. East of ditch.

Fd. OK, DCSO - July 8, 1971 - C.S. File 49/41

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22398)

The cor. of secs. 1 & 12 only, remonumented by the Douglas County Surveyors Office in 1959, perpetuated by Johnstone, in 1963, and remonumented by the Douglas County Surveyors Office in 1967, monumented with an iron post, 1¼" dia., firmly set, projecting 1" above ground, with no cap, from which the remains of an orig. bearing tree

continued next page

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A broken fir stump, size indeterminate, bears N.39°W., 49.8 ft., with scribe marks 24 R8 visible on open blaze. (Record, 51.5 ft. Rescribed by the Douglas County Surveyors Office in 1959.)

and remains of a bearing tree mkd. by the Douglas County Surveyors Office in 1959


A decayed fir stump, size indeterminate, bears S.71°W., 12.3 ft., with scribe marks BT visible on wood fragment lying alongside stump.

and bearing trees mkd. by Johnstone

A fir, 25" dia., bears S.6¼°W., 48.2 ft., with a healed blaze.

A fir, 27" dia., bears N.60½°W., 40.9 ft., with a healed blaze.

Remove the existing iron post, 36" long, from the ground and in its place, drive a finned aluminum rod, 36 ins. long, 3/4" dia., 39" in the ground, with aluminum cap mkd.



Cut the existing iron post in half and drive the pieces alongside the aluminum rod. Deposit a magnet in a white plastic case alongside the aluminum rod.

Corner is located approx. 2 ft. W. of bottom of ditch, approx. 12 ft. W. of a gravel road, 12 ft. wide, which bears S.16°E and N.16°W.

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Jeff Lorsung - 3/13/2019 (filed 1/28/2021 - C.S. File 67/48-17

Found - A 3/4" alum. rod by A.B. Skeesick, in 2005, firmly set buried 2" below the surface with a 3/4" dia. aluminum cap (properly) marked

An original BT by H. L. Chandler 1893 -

A 20" dia. x 2' tall mostly rotted fir stump bears N.39°W., 49.8 ft with scribe marks "2" and "8" visible.

and BTs by H. Johnstone in 1963 per C.S. File 51/163-

A 29" dia. G.Fir bears S.6¼°W., 48.2 ft with a fully healed blaze.

A 31" dia. G.Fir bears N.60½°W., 40.9 ft with a fully healed blaze.

New BTs- A 9" dia. D.Fir bears S.52°W., 22.4 ft, scribed "T24S R8W S12 CS" & "BT" on a double blaze.

A 14" dia. D.Fir bears N.34½°W., 44.5 ft, scribed "T24S R8W S1" & "CS BT" on a double blaze. CONT.

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 100574

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T24-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The corner falls 2 ft west of the ditch of a 12 ft wide gravel access road with mixed fir forest to the West of the monument.

All BTs have BT Tags attached. All new BTs have double blazed faces with bearing measured to the center of the tress at the root crown and distances measured to a 4" Mag Hub in the side and center of the root crown.

Geodetic coordinates

Latitude: 43°30'16.77" N.

Longitude: 123°35'06.90" W.

DATUM: Nad 83

SOURCE: GeoXT6000

Compass declination 14¾°E.