

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 6 (NW Tsp. Corner)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" Fir bears S.62°W., 64.1 ft.
8" Fir bears S.55°E., 11.2 ft.
Corner lies 2.28 ft. South of corner set by the County.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy -
Randall Smith and Stephen Flause, crew - March 5, 1984 - C.S.
File 62/16-7

Found - I.P. with properly mkd. brass cap protruding 12".
I.P. with properly mkd. brass cap protruding 8".
8" now 17" W.Fir with well healed double blaze bears
East. 32.8 ft. (DCSO 1966)
6" now 11" D.Fir with well healed single blaze bears
S.53°W., 74.2 ft. (DCSO 1966)
12" Fir with partially healed double blaze with
visible scribing "T24", bears S.62°W., 64.1 ft.
(1979)
8" Fir with partially healed double blaze, with
visible scribing "BT", bears S.55°E., 11.2 ft.
(1979)

The letters "AM" were added to the DCSO closing corner cap.
(Sketch in C.S. File)

BLM Dependent resurvey by A. Bert Skeesick, Cadastral
Surveyor and Robert H. Browning, Survey Tech, under special
instructions and Group No. 2104, surveyed July 2005/Jan. 2006
(DCSO records Vol. 57 Page(s) 22401-2)

The true point for the closing cor. of secs. 1 and 6, at the
intersection with the township line, established by Roberts,
in 1979, and is accepted as the cor., monumented with an iron
post, 2" dia., firmly set, projecting 9 ins. above ground,
with brass cap mkd.

PLS 1039
T23S R8W
S36
S1|S6
R8W R7W
1979

from which bearing trees mkd. by Roberts

A fir, 14" dia., bears S.57°E., 11.3 ft., with a healed
double blaze.

A fir, 23" dia., bears S.61½°W., 64.1 ft., with a healed
double blaze.

From this point, the orig. closing cor. of secs. 1 and 6,
T24S Rs 7 & 8W., established by Chandler in 1893,
remonumented by the Douglas County Surveyors Office in 1960,
continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

and perpetuated by the Douglas County Surveyors Office in 1966 and 1984, bears N.0°08'01"E., 2.17 ft., monumented with an iron post, 1½" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd.
from which the remains of the orig. bearing trees
A decayed fir stump, size indeterminate, bears S.57°E., 54.8 ft., with no marks visible
A sawed fir stump, 50" dia., bears S.9¼°W., 77.2 ft., with no marks visible. (Record, S.12°W., 79.2 ft.)
and BTs mkd. by the Douglas County Surveyors Office in 1966
A fir, 28" dia., bears N.88¾°E., 32.6 ft., with a healed blaze.
A fir, 20" dia., bears S.52¼°W., 73.0 ft., with a healed blaze.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 3/19/2019 (Filed 11/18/2021) - C.S. File 67/50-18

Found - 1979 Roberts ¾" dia., brass cap (properly mkd) on a 2" I.D. IP, projecting 8" above ground.
Possible evidence of 2 1893 OBTs -
A very rotted fir stump with no remaining blaze evidence; bears S.59°E., 53.7 ft. (as per computed 2005 BLM rec.)
An approx. 50" dia., sawn and rotted D.Fir stump with marks visible; bears S.9½°W. 75.0 ft. (as per computed 2005 BLM Rec.)
From the 1960 DCSO renewal a brass cap monument marking the 1893 corner position. -
A 2½" dia., on a 1" I.D. IP, projecting 13" above ground, bears N.0°18'10"E., 2.17 ft (as per BLM 2005 rec.) brass cap mkd:
COUNTY SURVEYORS OFFICE
AM CC T23S
S1|S6 T24S
R8W R7W
1960
Two 1966 BTs that formally referenced the fd 1960 BC -
A 28" dia. G.Fir with a FHSB; bears N.85¾°E. 33.0 ft
An 18" dia. D.Fir with a FHSB; bears S.54°W. 72.5 ft
Two 1979 Roberts BTs -
A 14" dia., D.Fir with FHSB; bears S.57°E., 11.3 ft. (as per 2005 BLM rec.)
A 21" dia., D.Fir with a FHSB; bears S.61½°W., 64.6 (rec. 64.1 ft)
New - 1960 BC monument and it 1966 BTs are now tied directly to the 1979 BC monument cor. position -
_____accepted by BLM in 2005_____ Cont.

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 6 (NW Tsp. Cor)

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

DCS0 GPS - 8/2021 - added 12/29/2021 - C.S. File 67/51-27
Lat: 43°31'09.48" N Long: 123°35'06.85" W