

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3264)

Set a post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N face, from which
A fir, 10" dia., bears N.30°W., 27 lks., mkd: ¼ S BT.
A fir, 18" dia., bears S.45°E., 21 lks., mkd: ¼ S BT.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22374-5)

The ¼ sec. cor. of secs. 7 and 18, determined at record bearing and dist. from the remaining orig. bearing tree
A fir, 20" dia., bears N.30°W., 17.8 ft., with fragmentary scribe and axe marks visible on a partially healed blaze and X mkd. in the bark. This tree also has BLM BT tag mkd. Healy 5NOV54 Shoemaker-79 and GLO Location Tag mkd. YT12-17-53 RBradley 6-20-55 DLynn 5/13/63 Henriksen, BB6-94 and GKerr.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 29" in the ground, below road surface, with brass cap mkd.
T24S R7W
¼ $\frac{S \ 7}{S \ 18}$
2005
from which
A fir, 19" dia., bears S.63¾°W., 38.7 ft., mkd. ¼ S18 BT