

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 6 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by Les Roberts - For: International Paper Co. - July 1979 - M 80-47

-----  
Set 1½" I. Pipe and brass cap, from which  
22" Fir bears S.57°W., 35.6 ft.  
14" W.Fir bears S.22°E., 7.6 ft.

Douglas Co. Surveyors Office - Stephen J Flause - Mike Koch - 9/5/2014 - C.S. File 67/41-60

-----  
Found - N¼ sec. 6 only, established by Roberts 1979; A 2½" dia., brass cap on 1" I.D. iron pipe is set plumb, protruding 8" above ground. Cap mkd:

LS 1939  
T23S R7W  
S 6 ¼  
T24S R7W  
1979

1979 BTs- A 22" Fir now a sawed and very rotted 20" dia., 2½ ft. tall fir stump with all the blaze evidence rotted away; bears S.57°W., 35.6 ft. (as per rec)  
A 14" W.Fir now a 16" dia., G.Fir (aka lowland White Fir) with a fully healed double blaze; bears S.22°E., 7.6 ft. (as per rec)  
S¼ Sec. 31, T23S, R7W; bears N.89½°E., 154.0 ft. (as per rec.) BC/IP

New - A G.Fir, 16" dia., scribed "¼ S6" "CSBT" on a double blaze; bears S.16½°W., 17.8 ft.  
A G.Fir, 13" dia., scribed "¼ S6 CS" "BT" on a double blaze; bears S.84°W., 14.3 ft.

Note - Monument is on a very gentle east slope in an old reprod. Forest of mixed fir with some cedar.  
Compass decl. 15½°E.