

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Cor Secs 31, 32; 5 & 6 T25-7

Alias 867010 Description M C Right bank Umpqua River
Alias _____ Description _____
Alias _____ Description _____
Alias 202100 Description WC ID # for Sec Cor

Monument is at bottom of fill slope on West side of County Road #33 and is approx. 650 ft. North from the Tye Access Bridge (USFS Rd. #25-7-5.1)

BLM dependent resurvey by Bryan S. Seibold & Wayne Rogers, Cadastral Surveyors, under Group #1862, surveyed Sept.-Dec. 1997 - (DCSO records Vol. 53 Page(s) 20301-2)

A witness cor. to the cor. of secs. 5, 6, 31 and 32, established by Bishop, in 1970, perpetuated by Geisler, in 1983, monumented with an iron post, 1½" diam., firmly set, projecting 10" above ground, and in a collar of stone, with brass cap mkd.

1970 T 24 S R 7 W 896
W C
31 | 32
6 | 5
T 25 S R 7 W

from which the remains of bearing trees mkd. by Bishop
An oak, 17" diam., bears S.61¼°W., 49 lks., with healed blaze.

A sawed cedar stump, 27" diam., bears N.48°W., 17½ lks., with healed double blazes.

and bearing trees mkd. by Geisler

An oak, 17" diam., bears N.88½°W., 50 lks., with healed double blazes.

An ash, 12" diam., bears N.8½°W., 28½ lks., with healed double blazes.

and a new bearing tree

The center trunk of a triple trunk alder, 11" diam., bears S. 29 3/4° E., 87 lks. dist., mkd. X BT.

From this point, the Douglas County Surveyor's Office horizontal control station "U14," at latitude 43°25'51.077" N., longitude 123°33'52.296"W. (NAD 1927), bears S.18°28'12"W, 11.178 chs. (mean bearing and sea level distance); monumented with a bronze disk, set flush in the bridge abutment of the Tye Access bridge, with top mkd. DOUGLAS CO. SURVEYORS OFFICE U14 1972.

N. 89° 55' 36" W., 2.159 chs

True point for the cor. of secs. 5, 6, 31 & 32, identical with the meander cor. of secs. 5 & 6, on the right bank of the Umpqua River, at projected bearing and Bishop's distance from the witness cor. to the cor. of secs. 5, 6, 31, and 32 (Shown on plat recorded in the Douglas County Surveyors Office map file, M33-68). Point falls in the Umpqua River and is not monumented; there is no remaining evidence of the original cor.

continued next page

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Cor Secs 31, 32; 5 & 6 T25-7

Alias 867010 Description M C Right bank Umpqua River
Alias _____ Description _____
Alias _____ Description _____
Alias 202100 Description WC ID # for Sec Cor

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Jeff Lorsung - March 5, 2019 (Filed 1/28/2021) - C.S. 67/48-16

Found - A 1" I.D. iron pipe by L. Bishop, firmly set, projecting 4" above a collar of stone with a 2½" dia. brass cap (properly) marked
BTs by L. Bishop per M 33-68 & C.S. 55/140 in 1970 -
A 19" diam. W.Oak bears S.61¼°W., 32.4 ft with a healed blaze. (1997 USBLM Rec. S.61¼°W. 49 lks.)
and a BT by Geisler in 1988 per M 93-79 -
A 21" dia. Ash bears N.8½°W., 18.8 ft with a healed blaze (Top of tree was broken out in a snow storm)
A 21" dia. W.Oak bears N.87½°W., 33.0 ft with a healed double blaze (1997 USBLM Rec N.88½°W. 50 lks)
New BT - A 22" dia. Ash bears N.72½°E., 3.3 feet scribed "X", "CSBT" on a double blaze.
Note - The corner falls on a fill slope on the West side of County Road 33 in mixed alder and ash timber.
All BTs have BT Tags attached. All new BTs have double blazed faces with bearing measured to the center of the trees at the root crown and distances measured to a 4" Mag Hub in the side and center of the root crown.

Geodetic coordinates
Latitude: 43°25'57.44" N. Longitude: 123°33'53.52"W.
Datum: NAD 83 Source: GeoXT6000
Compass declination 14¾°E.