

PRIMARY CORNER DESCRIPTION Sec Cor for 29, 30, 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3204)

Set post cor. secs. 29, 30, 31 and 32, from which
An Oak 30" dia., bears S.4°E., 240 lks. dist.
An Oak 36" dia., bears S.22°W., 270 lks. dist.
An Oak 30" dia., bears N.33°E., 222 lks. dist.
No tree convenient on sec. 30.

H.L.Eppstein, Surveyor - Wit: Ernie Short; Rudolph Ritzman - J.C. Clayton - March 29-31; April 1-3, 1926 - C.S. File 14/36 and Vol. 4 Page 3

Set corner from old BT in sec. 29. Found evidence of old BT in 31 and 32 but saw scribe marks except on BT in sec. 29. Set a 2" x 2 x 20" square iron pipe. Marked new BTs as follows:
B.Oak 14", N.41°W., 41.5 ft.
W.Oak 12", S.22°E., 51.7 ft.
W.Oak 15", S.52°W., 63.0 ft.

Larry D. Bishop - For: B.N. Glanville - Nov. 1970 - M 40-58

Found - 2"x2" square I.Pipe.
13" W.Oak S.22°E., 33.7 ft., opened face and verified age of scribing.
20" W.Oak S.54°W., 41.5 ft.
22" B.Oak N.41°W., 27.7 ft.
30" Oak down & mostly rotted away N.33°E., 146.5 ft.

Douglas Co. Surveyors Office - John M. Powell, and crew - Dec. 2, 1970 - C.S. File 49/41-61

Found - 2"x2"x20" sq. iron pipe at section corner, OK.
14" now 20" B.Oak N.41°W. (Rec. 41.5 ft.) 27.7 ft., shows good scars.
12" now 14" W.Oak S.22°E. (Rec. 51.7 ft.) 33.7 ft., opened for scribe "BT" reverse, face rotted.
15" now 18" W.Oak S.52°W. (Rec. 63.0 ft.) 41.5 ft., shows good scars.
These record distances must have been in links, as they check out for distance in feet. All bearings hit very good.
2"x2" Iron pipe is flush with ground, 1.0 ft. South of fence corner, fence runs N. and E.
New BTs- 8" D.Fir N.50°E., 8.3 ft. "T24S R7W S28 CS BT."
9" D.Fir S.37°E., 14.8 ft. "T24S R7W S33 CS BT."

(Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec Cor for 29, 30, 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. OK, May 1987 by H. Johnstone - M 104-16
Fd. OK, Jan. 1991 - M 111-25
Fd. OK, March 1995 - M 121-73

M.Smalley for Roseburg Forest Prod. Jan. 1999 - M131-12

Found 2" square iron pipe 1" below ground
BT's - 11" Fir, N.50°E., 8.3 ft. - healed
22" Oak, S.52°W., 41.5 ft. - healed
14" Fir, S.37°E., 14.8 ft. - stump, healed
14" Oak, S.22°E., 33.7 ft. - rotten face
20" Oak, N.41°W., 27.7 ft. - stump
Scribed- 14" Fir, N.18°E., 16.0 ft. "S29 BT"
16" Oak, N.24°W., 30.8 ft. "S30 BT"

Found OK by C. Sweeden, Aug. 2001 - 2001-0103 A&B
Fd. OK by D. Edwards, Dec. 2002 - M141-29
Fd. OK by K. DeGroot, Oct. 2003 - M143-17